Hi-Spot ES50 Home

ES50 HM 240V 35W 25° GU10 SV1

0021254



Cechy gamy

- Unique, patented, spiral faceted aluminised reflector
- Clear front lens for crisp sparkling light
- Integral safety fuse
- Ceramic base
- For use in mains voltage GU10 downlights, spotlights and luminaires
- Transformer free operation
- Average rated life 2500hrs

UV STOP

PRZEGLĄD PRODUKTÓW

Ordering number	0021254
Light colour	827 Homelight
Technology	Halogen
Energy class	E
Average life (Rated) (h)	3000
Lamp finish	Aluminium
Lamp shape	Reflector
Dimmable	Yes
Cap/Base	GU10
Type	PAR16 (GU10)
EAN code	5410288212548
CRI (Ra)	100
Beam angle(°)	25
Colour temperature (K)	2700
Useful luminous flux (Rated) (lm)	180
Watt (Nominal) (W)	35
Voltage (V)	240

Hi-Spot ES50 Home

ES50 HM 240V 35W 25° GU10 SV1

0021254

TABELA DANYCH

Dane główne

Ordering number	0021254
Technology	Halogen
Average life (Nominal) (h)	3000
Average life (Rated) (h)	3000
Energy saving lamp	No
Energy class	E
Lamp shape	Reflector
Lamp finish	Aluminium
Dimmable	Yes
Cap/Base	GU10
Type	PAR16 (GU10)
EAN code	5410288212548
E-number FI	4749547
Long description	Unique, patented, spiral faceted aluminised reflector. Clear front lens for crisp sparkling light. Integral safety fuse. Ceramic base. For use in mains voltage GU10 downlights, spotlights and luminaires. Transformer free operation. Average rated life 2500hrs
Product name	ES50 HM 240V 35W 25° GU10 SV1
Lamp mercury content (mg)	0
Starting time (max) (s)	0
Warm-up time to 60% of full light (max) (s)	Instant Full Light
Control gear required	No
Fixture rating	Open
IEC Reference	IEC 60357
IEC Reference 2	IEC 60432-3
IEC Reference 3	IEC 60630
Intended purpose	General lighting
No. of switching cycles before premature failure (min)	> 12000
Special purpose lamp	No
Transformer required	no
Sales pack quantity	10

Hi-Spot ES50 Home

ES50 HM 240V 35W 25° GU10 SV1

0021254

Dane optyczne

Light colour	827 Homelight
CRI (Ra)	100
Beam angle (Rated) (°)	25
Suitable for accent lighting	Yes
Beam angle(°)	25
Colour temperature (K)	2700
Useful luminous flux (Rated) (lm)	180
Lumen maintenance at end of nominal life (%)	80
Luminous flux (Nominal) (lm)	180
Peak intensity (cd)	500

Dane elektryczne

kWh per 1000 hours burning time	35
Watt (Rated) (W)	35
Watt (Nominal) (W)	35
Voltage (V)	240
Lamp power factor	1

Dane fizyczne


Weight (kg)	0.05
Lamp Length (mm) - C/L	55
Max. Lamp Diameter (mm) - D	50
Lamp dimension equal to filament lamp equivalent	Yes
Designed for optimum use in non standard conditions	No
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	6.20 x 4.80 x 4.80
Outer package dimensions (L x W x H) (cm)	50.00 x 27.00 x 14.00

Hi-Spot ES50 Home


ES50 HM 240V 35W 25° GU10 SV1


0021254

FOTOMETRIA



RYSUNEK TECHNICZNY





ETYKIETA ENERGETYCZNA

