

MASTER PL-C Xtra 4 Pin

MASTER PL-C Xtra 26W/830/4P 1CT/5X10CC

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

Product data

• General Information

Cap-Base	G24Q-3 [G24q-3]
Life To 50% Failures	33000 h
Preheat (Nom)	
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	96 %
LSF Preheat 16000 h Rated	94 %
LSF Preheat 20000 h Rated	90 %

• Light Technical

Colour Code	830 [CCT of 3000K]
Luminous Flux (Nom)	1800 lm
Luminous Flux (Rated) (Nom)	1800 lm
Colour Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	435
Chromaticity Coordinate Y (Nom)	400
Colour Temperature, horizontal (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	75 lm/W
Colour Rendering Index horiz (Nom)	82
Depreciation 2000 hrs	92 %
LLMF 4000 h Rated	88 %
Depreciation 5000 hrs	86 %
LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %
LLMF 16000 h Rated	79 %
LLMF 20000 h Rated	78 %

• Operating and Electrical

Power (Rated) (Nom)	26.0 W
Lamp Current (Nom)	0.300 A
Voltage (Nom)	100 V

• Temperature

Design Temperature (Nom)	28 °C

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Cap-Base Information	4P

• Approval and Application

Energy Efficiency Label	A
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	29 kWh

PHILIPS

MASTER PL-C Xtra 4 Pin


- Product Data

Full product code	871150089889070
Order product name	MASTER PL-C Xtra 26W/830/4P 1CT/5X10BOX
EAN/UPC - Product	8711500898890
Order code	89889070
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927906383014
Net Weight (Piece)	60.400 g
ILCOS Code	FSQ-26/30/1B-E-G24q=3


Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



G24q-2/G24q-3, 4P




PL-C Xtra 26W/830/4P

Product	D	D1	A	B	C
MASTER PL-C Xtra 26W/830/4P 1CT/5X10BOX	27.1 mm	27.1 mm	130.7 mm	149.0 mm	163.9 mm

MASTER PL-C Xtra 4 Pin

Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, April 19
data subject to change