

# MASTER PL-C 4 Pin

## MASTER PL-C 10W/830/4P 1CT/5X10BOX

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

## Product data

### • General Information

| | |
|---|---|
| Cap-Base | G24Q-1 [ G24q-1] |
| Life To 50% Failures Preheat (Nom) | 13000 h |
| LSF Preheat 2000 h Rated | 99 % |
| LSF Preheat 4000 h Rated | 98 % |
| LSF Preheat 6000 h Rated | 97 % |
| LSF Preheat 8000 h Rated | 90 % |

### • Light Technical

| | |
|---|---|
| Colour Code | 830 [ CCT of 3000K] |
| Luminous Flux (Nom) | 600 lm |
| Luminous Flux (Rated) (Nom) | 600 lm |
| Colour Designation | Warm White (WW) |
| Chromaticity Coordinate X (Nom) | 440 |
| Chromaticity Coordinate Y (Nom) | 403 |
| Colour Temperature, horizontal (Nom) | 3000 K |
| Luminous Efficacy (rated) (Nom) | 60 lm/W |
| Colour Rendering Index horiz (Nom) | 82 |
| Depreciation 2000 hrs | 92 % |
| LLMF 4000 h Rated | 87 % |
| Depreciation 5000 hrs | 83 % |
| LLMF 8000 h Rated | 81 % |

### • Operating and Electrical

| | |
|---|---|
| Power (Rated) (Nom) | 10.0 W |
| Lamp Current (Nom) | 0.190 A |

### • Temperature

| | |
|---|---|
| Design Temperature (Nom) | 28 °C |

### • Controls and Dimming

| | |
|---|---|
| Dimmable | Yes |

### • Mechanical and Housing

| | |
|---|---|
| Cap-Base Information | 4P |

### • Approval and Application

| | |
|---|---|
| Energy Efficiency Label | A |
| Mercury (Hg) Content (Nom) | 1.4 mg |
| Energy Consumption kWh/1000 h | 11 kWh |

### • Product Data

| | |
|---|---|
| Full product code | 871150062329470 |
| Order product name | MASTER PL-C 10W/830/4P 1CT/ 5X10BOX |
| EAN/UPC - Product | 8711500623294 |
| Order code | 62329470 |

PHILIPS

# MASTER PL-C 4 Pin


| | |
|---|---|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 50 |

| | |
|---|---|
| Material Nr. (12NC) | 927907083040 |
| Net Weight (Piece) | 41.400 g |
| ILCOS Code | FSQ-10/30/1B-E-G24q=1 |


## Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

## Dimensional drawing





G24q-1/G24q-2/G24q-3, 4P




PL-C 10W/830/4P

| Product | D | D1 | A | B | C |
|---|---|---|---|---|---|
| MASTER PL-C 10W/830/4P 1CT/5X10BOX | 27.1 mm | 27.1 mm | 75.5 mm | 95.0 mm | 109.9 mm |

## Photometric data



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

**www.philips.com/lighting**

2015, December 28
data subject to change