

HF-Performer Intelligent for TL5 HE/HO lamps

HF-Performer Intelligent 2 28/35/49/80 TL5 EII 220-240V

Intelligent, flat, slim, lightweight high-frequency electronic ballast for TL5 fluorescent lamps

Product data

• General Information

Application Code	EII
Lamp Type	TL5
Number Of Lamps	2 piece/unit
Number Of Products On MCB (16A Type B) (Nom)	8
Automatic Restart	Yes

• Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Ignition Method	Warm Start
Crestfactor (Max)	1.7
Ignition Time (Max)	5.0 s
Mains Voltage Performance (AC)	-8%-+6%
Mains Voltage Safety (AC)	-10%-+10%
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.37 ms
Constant Wattage Deviation	-2%/+2%
Ballast Factor (Nom)	1.00
Power Losses (Nom)	6.8-11.6 W
Inrush Current Peak (Max)	31 A

• Wiring

Connector Type Input Terminals	Insert
Cable Capacity Output Wires Mutual (Nom)	150 pF
Connector Type Output Terminals	Insert
Cable Length Hot Wiring	0.75 m
Wire Striplength	8.0-9.0 mm
Input Terminal Cross Section	0.50-1.00 mm²
Output Terminal Cross Section	0.50-1.00 mm²
Cable Capacity Output Wires To Earth (Nom)	150 pF

• System characteristics

Rated Ballast-Lamp Power	28/35/49/80 W
Rated Lamp Power On TL5	28/35/49/80 W
System Power On TL5	36.6/45.4/59.1/94.9 W
Lamp Power On TL5	29/36.2/49.4/83.7 W
Power Loss On TL5	7.6/9.2/9.7/11.2 W

• Temperature

T-Ambient (Max)	50 °C
T-Ambient (Min)	-25 °C
T-Storage (Max)	80 °C
T-Storage (Min)	-40 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C

PHILIPS

HF-Performer Intelligent for TL5 HE/HO lamps

T-Ignition (Max)	50 °C
T-Ignition (Min)	-25 °C

• Mechanical and Housing

Housing	L 425x30x22

• Emergency Operation

Battery Voltage Lamp Operation	198-276


• Approval and Application


Energy Efficiency Index	A2
EMI 9 kHz ... 30 MHz	EN55015
EMI 30 MHz ... 1000 MHz	EN 55022 Class B
Safety Standard	IEC 61347-2-3
Performance Standard	IEC 60929
Quality Standard	ISO 9000:2000
Environmental Standard	ISO 14001
Harmonic Current Emission Standard	IEC 61000-3-2
EMC Immunity Standard	IEC 61547
Vibration Standard	IEC 68-2-6 Fc
Bumps Standard	IEC 68-2-29 Eb
Humidity Standard	EN 61347-2-3 clause 11
Approval Marks	CE marking ENEC certificate VDE-EMV certificate
Temperature Marking	Yes
Emergency Standard	IEC 60598-2-22
Hum And Noise Level	Inaudible


• Product Data

Full product code	872790086250800
Order product name	HF-Performer Intelligent 2 28/35/49/80 TL5 EII
EAN/UPC - Product	8711500881199
Order code	86250800
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700652666
Net Weight (Piece)	0.380 kg

Dimensional drawing







HF-Pi 2 28/35/49/80 TL5 EII 220-240V

Product	D1	C1	A1	A2	B1
HF-Performer Intelligent 2 28/35/49/80 TL5 EII	4.2 mm	22 mm	425 mm	415 mm	30 mm

Photometric data

Ballast type	Lamp type	Lamp power		Ta = 40°C	Ta = 50°C	Ta = 60°C	Remarks Ta max = 63°C
HF-Pi 2 28/35/49/80 TL5 EII 220-240V	TL5 HE	28W					
	TL5 HE	35W	Tc	=53°C	=63°C	=72°C	75°C
	TL5 HE	49W	Lifetime	100,000 Hrs	100,000 Hrs	100,000 Hrs	100,000 Hrs
	TL5 HO	49W					
	Lamp type	Lamp power		Ta = 40°C	Ta = 50°C	Ta = 60°C	Remarks Ta max = 62°C
	TL5 HO	80W	Tc	=57°C	=64°C	=73°C	75°C
			Lifetime	100,000 Hrs	100,000 Hrs	83,000 Hrs	72,000 Hrs



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 23
data subject to change