

HF-Essential II for TL5/TL-D

HF-E 1/2 54 TL5 II 220-240V 50/60Hz

Essentially smart and reliableHF-Essential II is the most cost-effective solution for reliably operation of a fluorescent lamp. It is also the ideal entry-level product for electromagnetic system users who want to take advantage of the benefits provided by electronic ballasts.The cost-saving and reliable HF-Essential II is energy efficiency class A2, and its robust design meets all relevant international safety and performance standards.HF- Essential II is the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting and office lighting, parking garages, warehouses and other applications.

Product data

• General Information

Lamp Type	TL5 II
Number Of Lamps	1/2 piece/unit
Number Of Products On MCB (16A Type B) (Nom)	20
Automatic Restart	Yes

• Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Operating Frequency (Nom)	44.3 kHz
Crestfactor (Nom)	1.8
Power Factor 100% Load (Nom)	0.98
Preheat Time	1.7 s
Mains Voltage Performance (AC)	202-254V-8%-+6%
Mains Voltage Safety (AC)	198-264V-10%-+10%
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.3 ms
Ballast Factor (Nom)	0.97
Power Losses (Nom)	4.6/8.24 W
Inrush Current Peak (Max)	24 A

• Wiring

Connector Type Input Terminals	Insert
Cable Capacity Output Wires Mutual (Max)	200 pF
Connector Type Output Terminals	Insert
Cable Length Hot Wiring	0.75 m
Wire Striplength	8.0-9.0 mm
Dual Fixture Master/ Slave	Possible, lamp wires 0.75m max. length [Master/Slave operation possible]
Input Terminal Cross Section	0.50-1.50 mm²
Output Terminal Cross Section	0.50-1.50 mm²
Cable Capacity Cold Output Wires - Earth (Max)	200 pF
Cable Capacity Hot Output Wires - Earth (Max)	200 pF

• System characteristics

Rated Ballast-Lamp Power	54/55/58 W
Lamp Power On TL5	53.3-47.75-47.91 W

• Temperature

T-Ambient (Max)	50 °C

PHILIPS

T-Ambient (Min)	0 °C
T-Storage (Max)	80 °C
T-Storage (Min)	-40 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C

- Mechanical and Housing

Housing	L280x30x22,7

- Emergency Operation

Nominal Light Output After 60 Seconds	100% of EBLF
Normal Operating Voltage (DC)	220-240 V
Battery Voltage Guaranteed Operation	176-275 V
Battery Voltage Guaranteed Ignition	186-275 V
Emergency Ballast Lumen Factor (EBLF) (Nom)	0.7 %
Nominal Light Output After 5 Seconds	50% of EBLF


- Approval and Application

Energy Efficiency Index	A2
EMI 9 kHz ... 30 MHz	EN55015
Vibration Standard	IEC 60068-2-6:2007-Fc
Bumps Standard	IEC 60068-2-29:1993-Eb
Approval Marks	CE marking KEMA Keur certificate CB Certificate RoHS Compliant
Hum And Noise Level	< 30 dB(A)

- Product Data


Full product code	871829177066400
Order product name	HF-E 1/2 54 TL5 II 220-240V 50/60Hz
EAN/UPC - Product	8718291770664
Order code	913713040866
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	913713040866
Net Weight (Piece)	0.125 kg

Dimensional drawing



HF-E 1/2 54 TL5 II 220-240V 50/60Hz

Product	D1	C1	A1	A2	B1
HF-E 1/2 54 TL5 II 220-240V 50/60Hz	4.2 mm	22.7 mm	280.0 mm	270.0 mm	30.0 mm



HF-E TL5 II / TL-D II 2 Lamps



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 23
data subject to change