


PrimaVision Compact for CDM

HID-PV C 70 /I CDM 220-240V 50/60Hz

High-quality, compact and lightweight HID electronic gear for optimal and reliable performance of 20, 35, 50 and 70 W CDM lamps

Product data

• General Information

Type Version	NG
Lamp Type	CDM
Number Of Lamps	1 piece/unit
Suitable For Outdoor Use	No
Number Of Products On MCB (16A Type B) (Nom)	20
Automatic Restart	Yes

• Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Operating Frequency (Nom)	0.14 kHz
Power Factor 100% Load (Nom)	0.95
Ignition Voltage (Max)	4.0 kV
Ignition Switch-Off Time (Nom)	18 min
Mains Voltage Performance (AC)	-10%-+6%
Mains Voltage Safety (AC)	-18%-+10%
Earth Leakage Current (Max)	0.25 mA
Inrush Current Width	0.33 ms
Constant Wattage Deviation	-3%/+3%
Power Losses (Nom)	7.0 W
Inrush Current Peak (Max)	33 A

• Wiring

Cable Capacity	150 pF
Output Wires Mutual (Nom)	
Cable Length From Device To Lamp	2.0 m
Ballast Contact Wire Cross Section	0.50-2.50 mm²
Connector Type	Insert

• System characteristics

Rated Ballast-Lamp Power	70 W

• Temperature

T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	75 °C
T-Storage (Min)	-25 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C

• Mechanical and Housing

Housing	/I

• Approval and Application

Active Temperature Protection	Yes

PHILIPS


PrimaVision Compact for CDM


EMI 9 kHz ... 300 MHz	CISPR 15 ed 7.2
Safety Standard	EN 61347-2-12
Quality Standard	ISO 9000:2000
Environmental Standard	ISO 14001
Harmonic Current Emission Standard	EN 61000-3-2
EMC Immunity Standard	EN 61547
Vibration Standard	IEC 68-2-6 Fc
Bumps Standard	IEC 68-2-29 Eb
Humidity Standard	IEC 928-13
Approval Marks	CE marking ENEC certificate
Temperature Marking	F
Hum And Noise Level	37 dB(A)


- Product Data

Full product code	872790085988100
Order product name	HID-PV C 70 /I CDM 220-240V 50/60Hz NG
EAN/UPC - Product	8711500881717
Order code	85988100
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700653266
Net Weight (Piece)	0.360 kg

Dimensional drawing







HID-PV CDM Gen 4.3

HID-PV C 70 /I CDM 220-240V 50/60Hz NG

Product	D1	C1	A1	A2	B1
HID-PV C 70 /I CDM 220-240V 50/60Hz NG	4.8 mm	34.5 mm	188.0 mm	170.0 mm	82.7 mm

© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 23
data subject to change