

HalogenA IDE

HalogenA IDE 1000W E40 230V CL 1CT/6

Mains-voltage high-wattage double-envelope giving a white halogen light

Product data

• General Information

Cap-Base	E40 [E40]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X

• Light Technical

Luminous Flux (Nom)	24000 lm
Luminous Flux (Rated) (Nom)	24000 lm
Colour Temperature, horizontal (Nom)	2900 K
Luminous Efficacy (rated) (Nom)	24 lm/W
Colour Rendering Index horiz (Nom)	100
LLMF At End Of Nominal Lifetime (Min)	80 %

• Operating and Electrical

Power (Rated) (Nom)	1000.0 W
Lamp Current (Nom)	4.35 A
Starting Time (Nom)	0.0 s
Warm Up Time To 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	230 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Bulb Finish	Clear (CL)

• Approval and Application

Energy Efficiency Label	C
Energy Consumption kWh/1000 h	1000 kWh


• Product Data

Full product code	871150049128210
Order product name	HalogenA IDE 1000W E40 230V CL 1CT/6
EAN/UPC - Product	8711500491282
Order code	49128210
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	923900244240
Net Weight (Piece)	158.000 g
ILCOS Code	HEGT-1000-230-e40


PHILIPS

HalogenA IDE

Dimensional drawing



E27/E40, T38



IDE 1000W E40 230V T38 CL

Product	D	C
HalogenA IDE 1000W E40 230V CL 1CT/6	38.5 mm	256 mm

© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting