

Brilliantline Alu

Brilliantline Alu 50W GU5.3 12V MR16 36D 1CT/10X5F

Superior-quality low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Aluminum coating prevents heat in the backlight.

PHILIPS

Brilliantline Alu

Product data

• General Information

Cap-Base	GU5.3 [GU5.3]
Philips Code	14717
Operating Position	UNIVERSAL [Any or Universal (U)]
ANSI Code Halogen	BAB
Nominal Lifetime (Nom)	4000 h
Switching Cycle	16000X

• Light Technical

Beam Angle (Nom)	36 °
Luminous Flux (Rated) (Nom)	780 lm
Luminous Intensity (Max)	2100 cd
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100
LLMF At End Of Nominal Lifetime (Min)	80 %
Luminous Flux In 90° Cone (Rated)	780 lm

• Operating and Electrical

Power (Rated) (Nom)	50.0 W
Lamp Current (Nom)	4.25 A
Starting Time (Nom)	0.0 s
Warm Up Time To 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	12 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Bulb Finish	Clear

• Approval and Application

Energy Efficiency Label (EEL)	B
Energy Consumption kWh/1000 h	53 kWh


• Luminaire Design Requirements

Bulb Temperature (Max)	250 °C
Cap-Base Temperature (Max)	350 °C

• Product Data

Full product code	871150043079360
Order product name	Brilliantline Alu 50W GU5.3 12V MR16 36D 1CT/10X5F
EAN/UPC - Product	8711500430793
Order code	924057417101
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924057417101
Net Weight (Piece)	30.000 g
ILCOS Code	HAGS-50-12-GU5.3-50/36

Dimensional drawing




GU5.3, MR16

ALU 14717 50W GU5.3 12V MR16 36D

Product	D	C
Brilliantline Alu 50W GU5.3 12V MR16 36D 1CT/10X5F	51 mm	46 mm

Dimensional drawing



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change