

Plusline ES Compact

Plusline ES Compact 78mm 2y 120W R7s 230V 1BB

Mains-voltage halogen linear lamp with superior quality and reliability. Offers very long lifetime and crisp halogen light. Ideal solution for decorative luminaires.

Product data

• General Information

Cap-Base	R7S [R7s]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X

• Light Technical

Luminous Flux (Nom)	2220 lm
Luminous Flux (Rated) (Nom)	2220 lm
Colour Temperature, horizontal (Nom)	2900 K
Luminous Efficacy (rated) (Nom)	18.5 lm/W
Colour Rendering Index horiz (Nom)	100
LLMF At End Of Nominal Lifetime (Min)	80 %

• Operating and Electrical

Power (Rated) (Nom)	120 W
Lamp Current (Nom)	0.52 A
Wattage Equivalent	150 W
Starting Time (Nom)	0.0 s
Warm Up Time To 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	230 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Bulb Finish	Clear (CL)
Cap-Base Information	18

• Approval and Application

Energy Efficiency Label	D
Energy Consumption kWh/1000 h	120 kWh

• Luminaire Design Requirements


Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C

• Product Data


Full product code	872790085223300
Order product name	Plusline ES Compact 78mm 2y 120W R7s 230V 1BB
EAN/UPC - Product	8727900852233
Order code	85223300
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	924587244210
Net Weight (Piece)	7.000 g

PHILIPS

Dimensional drawing



R7s/18, T11



DEComp 78mm 2y 120W R7s/18 230V T11 CL

Product	D	B	B	B	C
Plusline ES Compact 78mm 2y 120W R7s 230V 1BB	11 mm	76.5 mm	74.9 mm	73.3 mm	78 mm

© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting