

MASTERColour CDM-Rm Elite Mini

MASTERColour CDM-Rm Elite Mini 35W/930 GX10 MR16 10D

Mini, very high-efficiency Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Product data

• General Information

Cap-Base	GX10 [GX10]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life To 5% Failures (Nom)	9000 h
Life To 10% Failures (Nom)	10000 h
Life To 20% Failures (Nom)	12000 h
Life To 50% Failures (Nom)	15000 h
ANSI Code HID	C130/O
Switching Cycle	1350X

• Light Technical

Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	10 °
Beam Angle Technical (Nom)	12 °
Beam Angle Technical (Max)	15 °
Beam Angle Technical (Min)	9 °
Luminous Intensity (Min)	13200 cd
Luminous Intensity (Nom)	17500 cd
Beam Description	-
Lumen Maintenance 12000 h (Nom)	85 %
Lumen Maintenance 2000 h (Nom)	95 %
Lumen Maintenance 4000 h (Nom)	93 %
Chromaticity Coordinate X (Nom)	0.439
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	61 lm/W
Color Rendering Index (Min)	88
Color Rendering Index (Nom)	91
LLMF At End Of Nominal Lifetime (Nom)	86 %
Luminous Flux In 90° Cone (Rated)	2150 lm

• Operating and Electrical

Power (Rated) (Nom)	39 W
Re-Ignition Time (Min) (Max)	15 min
Warm Up Time To 60% Light (Nom)	120 s
Ignition Time (Max)	30 s
Voltage (Max)	95 V
Voltage (Min)	79 V
Voltage (Nom)	87 V

• Controls and Dimming

Dimmable	No
Run-Up Time 90% (Max)	3 min

PHILIPS

MASTERColour CDM-Rm Elite Mini

- Mechanical and Housing

Bulb Finish	-

- Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	4.7 mg
Energy Consumption kWh/1000 h	43 kWh

- UV

Pet (Niosh) (Min)	8 h/500lx
Damage Factor D/fc (Max)	0.4

- Luminaire Design Requirements

Reflector Neck Temperature (Max)	315 °C


- Product Data

Full product code	871829116296400
Order product name	MASTERColour CDM-Rm Elite Mini 35W/930 GX10 MR16 10D
EAN/UPC - Product	8718291162964
Order code	928194605330
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928194605330
Net Weight (Piece)	0.048 kg
ILCOS Code	MRS/UB-35/930-H-GX10-51/54.5/10

Warnings and Safety

- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035).
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




CDM-Rm, GX10, MR16

CDM-Rm 35W/930 GX10 MR16 10D


Product	D	D	C	C	C1	A
MASTERColour CDM-Rm Elite Mini 35W/930 GX10 MR16 10D	51 mm	50 mm	65.4 mm	62.75 mm	60.9 mm	59 mm

MASTERColour CDM-Rm Elite Mini

Dimensional drawing



Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, March 11
data subject to change