

HPI-T

HPI-T 2000W/542 E40 380V 1SL/4

Quartz metal halide lamps with clear outer bulb

Product data

• General Information

Cap-Base	E40 [E40]
Operating Position	P20 [Parallel +/-20D or Horizontal(HOR)]
Life To 5% Failures (Nom)	3000 h
Life To 10% Failures (Nom)	5500 h
Life To 20% Failures (Nom)	8000 h
Life To 50% Failures (Nom)	12000 h
System Description	High Output

• Light Technical

Color Code	542 [CCT of 4200K]
Luminous Flux (Rated) (Min)	195000 lm
Luminous Flux (Rated) (Nom)	210000 lm
Color Designation	Cool White (CW)
Lumen Maintenance 10000 h (Nom)	75 %
Lumen Maintenance 2000 h (Nom)	90 %
Lumen Maintenance 5000 h (Nom)	80 %
Chromaticity Coordinate X (Nom)	387
Chromaticity Coordinate Y (Nom)	403
Correlated Color Temperature (Nom)	3800 K
Luminous Efficacy (rated) (Nom)	107 lm/W
Color Rendering Index (Nom)	65

• Operating and Electrical

Lamp supply voltage	380 V [380]
Power (Rated) (Nom)	1955.0 W
Lamp Current Run-Up (Max)	15.3 A
Lamp Current (EM) (Nom)	9.1 A
Ignition Peak Voltage (Max)	5000 V
Ignition Supply Voltage (Min)	342 V
Ignition Time (Max)	30 s
Voltage (Max)	247 V
Voltage (Min)	217 V
Voltage (Nom)	232 V

• Controls and Dimming

Dimmable	No

• Mechanical and Housing

Bulb Finish	Clear

• Approval and Application

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	256 mg
Energy Consumption kWh/1000 h	2150 kWh

PHILIPS

HPI-T

- Luminaire Design Requirements

Bulb Temperature (Max)	600 °C
Cap-Base Temperature (Max)	300 °C

- Product Data


Full product code	871150020235245

Order product name	HPI-T 2000W/542 E40 380V 1SL/4
EAN/UPC - Product	8711500202352
Order code	928074209228
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928074209228
Net Weight (Piece)	572.300 g
ILCOS Code	MT-2000/42/2B-H-E40-/H


Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




HPI-T, 1000W, E40



HPI-T 2000W/542 HO E40 380V

Product	D	O	L	C
HPI-T 2000W/542 E40 380V 1SL/4	101.5 mm	120 mm	267 mm	430 mm

Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, March 7
data subject to change