

MASTER CosmoWhite CPO-TW & CPO-TW Xtra

MASTER CosmoWhite CPO-TW Xtra 45W/628 PGZ12

New-generation ceramic metal halide lamps used in Outdoor offering efficient and pleasant white light

Product data

• General Information

Cap-Base	PGZ12 [PGZ12]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life To 5% Failures (Nom)	21500 h
Life To 10% Failures (Nom)	24000 h
Life To 20% Failures (Nom)	27000 h
Life To 50% Failures (Nom)	32000 h
ANSI Code HID	C196/E
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	99 %
LSF 16000 h Rated	99 %
LSF 20000 h Rated	97 %
LSF 24000 h Rated	90 %
LSF 30000 h Rated	63 %

• Light Technical

Color Code	628 [CCT of 2800K]
Luminous Flux (Rated) (Nom)	4950 lm
Color Designation	White (WH)
Chromaticity Coordinate X (Nom)	459
Chromaticity Coordinate Y (Nom)	412
Luminous Efficacy (rated) (Nom)	110 lm/W
Color Rendering Index (Min)	63
Color Rendering Index (Nom)	66
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	90 %
LLMF 6000 h Rated	90 %
LLMF 8000 h Rated	90 %
LLMF 12000 h Rated	89 %
LLMF 16000 h Rated	87 %
LLMF 20000 h Rated	86 %
LLMF 24000 h Rated	84 %
LLMF 30000 h Rated	82 %

• Operating and Electrical

Power (Rated) (Nom)	45.0 W
Ignition Peak Voltage (Max)	5000 V
Re-Ignition Time (Min) (Max)	900 s
Ignition Time (Max)	30 s
Voltage (Max)	98 V
Voltage (Min)	84 V
Voltage (Nom)	91 V

• Controls and Dimming

Dimmable	Yes
Run-Up Time 90% (Max)	4 min

• Mechanical and Housing

Bulb Finish	Clear

PHILIPS

MASTER CosmoWhite CPO-TW & CPO-TW Xtra

- Approval and Application

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	2.0 mg
Energy Consumption kWh/1000 h	49 kWh

- UV

Pet (Niosh) (Min)	8 h/500lx
Pet (Niosh) (Nom)	20 h/500lx
Damage Factor D/fc (Nom)	0.21

- Luminaire Design Requirements

Bulb Temperature (Max)	380 °C
Cap-Base Temperature (Max)	250 °C


- Product Data

Full product code	871829115001500
Order product name	MASTER CosmoWhite CPO-TW Xtra 45W/628 PGZ12
EAN/UPC - Product	8718291150015
Order code	928083805127
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928083805127
Net Weight (Piece)	0.034 kg
ILCOS Code	MT-45/628-H-PGZ12-20/132


Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




CPO-TW Xtra 45 W, 60 W, 90 W, 140 W /628, /728 PGZ12



CPO-TW Xtra 45W/628 PGZ12

Product	D	D	O	L	C
MASTER CosmoWhite CPO-TW Xtra 45W/628 PGZ12	20 mm	19 mm	14 mm	59 mm	132 mm

Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting