

MASTER SON-T PIA Plus

MASTER SON-T PIA Plus 70W/220 E27 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime

Product data

• General Information

Cap-Base	E27
Operating Position	UNIVERSAL [Any or Universal (U)]
Life To 5% Failures (Nom)	17000 h
Life To 10% Failures (Nom)	20000 h
Life To 20% Failures (Nom)	23500 h
Life To 50% Failures (Nom)	30000 h
ANSI Code HID	-
System Description	External Ignitor
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	99 %
LSF 16000 h Rated	96 %
LSF 20000 h Rated	90 %

• Light Technical

Color Code	220 [CCT of 2000K]
Luminous Flux (Rated) (Nom)	6600 lm
Lumen Maintenance 2000 h (Nom)	90 %
Lumen Maintenance 20000 h	81 %
Lumen Maintenance 5000 h (Nom)	86.5 %
Chromaticity Coordinate X (Nom)	540
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2000 K
Luminous Efficacy (rated) (Nom)	91 lm/W
Color Rendering Index (Max)	25
LLMF 2000 h Rated	90 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	86 %
LLMF 8000 h Rated	85 %
LLMF 12000 h Rated	83 %
LLMF 16000 h Rated	82 %
LLMF 20000 h Rated	81 %

• Operating and Electrical

Lamp supply voltage	230 V [230]
Power (Rated) (Nom)	73.0 W
Lamp Current (EM) (Nom)	0.975 A
Ignition Supply Voltage (Max)	198 V
Ignition Peak Voltage (Max)	1800 V
Re-Ignition Time (Min) (Max)	30 s
Ignition Time (Max)	5 s
Voltage (Max)	105 V
Voltage (Min)	75 V
Voltage (Nom)	90 V

• Controls and Dimming

Dimmable	Yes
Run-Up Time 90% (Max)	4 min

PHILIPS

MASTER SON-T PIA Plus

- Mechanical and Housing

Bulb Finish	Clear
Cap-Base Information	-

- Approval and Application

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	12 mg
Energy Consumption kWh/1000 h	80 kWh

- Luminaire Design Requirements

Bulb Temperature (Max)	350 °C
Cap-Base Temperature (Max)	200 °C


- Product Data

Full product code	871150019266015
Order product name	MASTER SON-T PIA Plus 70W/220 E27 1SL/12
EAN/UPC - Product	8711500192660
Order code	928152700028
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928152700028
Net Weight (Piece)	0.048 kg
ILCOS Code	ST-70-H/S-E27

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



SON-T PIA Plus, E39/E40





SON-T PIA PLUS 70W E E27

Product	D	O	L	C
MASTER SON-T PIA Plus 70W/220 E27 1SL/12	36 mm	42 mm	104 mm	156 mm

MASTER SON-T PIA Plus

Photometric data





© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, March 7
data subject to change