

CorePro LEDcandle

CorePro LEDcandle ND 5.5-40W E14 840 B35 FR

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E14 holder and is an attractive product for chandeliers. LEDlamps deliver huge energy savings and minimize maintenance cost.

PHILIPS

CorePro LEDcandle

Product data

- General Information

Cap-Base	E14 [E14]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	5.5-40W

- Light Technical

Colour Code	840 [CCT of 4000K (841)]
Luminous Flux (Nom)	520 lm
Luminous Flux (Rated) (Nom)	520 lm
Colour Designation	White (WH)
Colour Temperature, horizontal (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	94.5 lm/W
Color Consistency	6 steps
Colour Rendering Index horiz (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

- Operating and Electrical

Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	5.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	40 W
Starting Time (Max)	0.5 s
Warm Up Time To 60% Light (Nom)	instant full light
Power Factor (Nom)	0.5
Voltage (Nom)	220-240 V

- Temperature

T-Case Maximum (Nom)	80 °C

- Controls and Dimming

Dimmable	No

- Mechanical and Housing

Bulb Finish	Frosted (FR)


- Approval and Application

Suitable For Accent Lighting	No
Energy Efficiency Label	A+
Energy Consumption kWh/1000 h	6 kWh

- Product Data

Full product code	871869654356600
Order product name	CorePro LEDcandle ND 5.5-40W E14 840 B35 FR
EAN/UPC - Product	8718696543566
Order code	54356600
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001205802
Net Weight (Piece)	0.040 kg

Dimensional drawing




E14 B35, B39


LED ND 5.5-40W E14 840 B35 FR

Product	D	C
CorePro LEDcandle ND 5.5-40W E14 840 B35 FR	35 mm	106 mm

Dimensional drawing



Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, April 10
data subject to change