


HID-Basic BSN/BMH MK4 semi-parallel for SON/CDO/CDM/MH/HPI

BSN 70 K407-ITS 230/240V 50Hz BC1-118

Impregnated electromagnetic copper ballasts for use with an external semi-parallel ignitor for CDM, CDO, MH, HPI (Plus) and SON lamps

Product data

• General Information

Application Code	K407-ITS
Design	BC1-118
Lamp Type	SON/CDO
Number Of Lamps	1 piece/unit

• Operating and Electrical

Input Voltage	230 V (default) or 240 V
Input Frequency	50 Hz
Power Factor 100% Load (Nom)	0.85
Mains Voltage Performance (AC)	-8%-+6%
Mains Voltage Safety (AC)	-10%-+10%
Input Current With PF Correction	0.45 A
Input Current Without PF Correction	0.98 A
Power Factor Without PF Compensation (Nom)	0.35
Power Losses (Nom)	13.3/13.6 W

• Wiring

Wire Striplength	7.0 mm
Ballast Contact Wire Cross Section	1.00-2.50 mm²
Connector Type	Screw

• System characteristics

Capacitor	12µF/250V
Rated Ballast-Lamp Power	70 W
Recommended Ignitor	for SON/CDO/CDM lamps ignitor SKD 578 (913700655366) or series digital SUD10 (913700195891)

• Temperature

T-Storage (Max)	130 °C
T-Storage (Min)	-30 °C
T-Winding (Max)	140 °C
Delta-T Normal Conditions	80/80 °C

• Approval and Application

Active Temperature Protection	Yes


• Product Data


Full product code	872790088694800
Order product name	BSN 70 K407-ITS 230/240V 50Hz BC1-118
EAN/UPC - Product	8711500881533
Order code	88694800
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700277026
Net Weight (Piece)	1.230 kg

PHILIPS

HID-Basic BSN/BMH MK4 semi-parallel for SON/CDO/CDM/MH/HPI

Dimensional drawing





BSN 70 K407-ITS 230/240V 50Hz BC1-118

Product	D1	C1	A1	A2	B1
BSN 70 K407-ITS 230/240V 50Hz BC1-118	6.2 mm	52.0 mm	118.0 mm	94.0 mm	61.0 mm

© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, March 14
data subject to change