


HID-Basic BHL for HPL/HPI

BHL 50/80 K407 230/240V 50Hz BC1-118

Impregnated electromagnetic copper/iron ballasts for HPL and HPI (Plus) lamps

Product data

• General Information

Application Code	K407
Design	BC1-118
Lamp Type	HPL/HPI
Number Of Lamps	1 piece/unit

• Operating and Electrical

Input Voltage	230 V (default) or 240 V
Input Frequency	50 Hz
Power Factor 100% Load (Nom)	0.85
Mains Voltage Performance (AC)	-8%-+6%
Mains Voltage Safety (AC)	-10%-+10%
Input Current With PF Correction	0.85 A

• Wiring

Wire Striplength	7.0 mm
Ballast Contact Wire Cross Section	2.5 mm²
Connector Type	Screw

• System characteristics

Capacitor	8µF/250V
Rated Ballast-Lamp Power	50/80 W
Recommended Ignitor	no ignitor for HPL-N

• Temperature


T-Storage (Max)	130 °C
T-Storage (Min)	-30 °C
T-Winding (Max)	130 °C
Delta-T Normal Conditions	55/80 °C

• Product Data

Full product code	872790094007700
Order product name	BHL 50/80 K407 230/240V 50Hz BC1-118
EAN/UPC - Product	8727900940077
Order code	94007700
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700286126
Net Weight (Piece)	0.955 kg

PHILIPS

Dimensional drawing





BHL 50/80 K407 230/240V 50Hz BC1-118

Product	D1	C1	A1	A2	B1
BHL 50/80 K407 230/240V 50Hz BC1-118	6.2 mm	52.0 mm	118.0 mm	94.0 mm	61.0 mm

© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting