

MASTER TL-D Super 80

MASTER TL-D Super 80 36W/865 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Benefits

• General Information

Cap base	G13 [G13]
Life to 10% failures (nom.)	12000 h
Life to 50% failures (nom.)	15000 h
Life to 50% failures preheat (nom.)	20000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	89 %
LSF 16000 h Rated	33 %
LSF 20000 h Rated	2 %

• Light Technical

Lamp Luminous Flux 25°C EL (Nom)	3250 lm
Lamp Luminous Flux (Nom)	3250 lm
Colour Designation	Cool Daylight
Chromaticity coordinate X (nom.)	313
Chromaticity coordinate Y (nom.)	337
Colour Temperature, horizontal (Nom)	6500 K
Lamp Luminous Efficacy EM (Nom)	90 lm/W
Colour Rendering Index,horiz (Nom)	85
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %

• Operating and Electrical

Power (Rated) (Nom)	36.0 W
Lamp current (nom.)	0.440 A

• Temperature

Design temperature (nom.)	25 °C

• Controls and Dimming

Dimmable	yes

• Mechanical and Housing

Cap base information	Green Plate

• Approval and Application

Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	2.0 mg
Energy Consumption kWh/1000 h	42 kWh

• Product Data

Full product code	871150063207440
Order product name	MASTER TL-D Super 80 36W/865 1SL/25

PHILIPS

MASTER TL-D Super 80


EAN/UPC – product	8711500632074
Order code	927921086544
Numerator – quantity per pack	1
Numerator – packs per outer box	25

Material no. (12NC)	927921086544
Net weight (piece)	124.600 g
ILCOS Code	FD-36/65/1B-E-G13

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




TL-D 36W/865


Product	D	A	B	B	C
MASTER TL-D Super 80 36W/865 1SL/25	28 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm

G13, T8



Photometric data





© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change