

TL-X XL

TL-X XL 20W/33-640 SLV/25

Single-pin low-pressure mercury discharge lamps with a tubular 38 mm envelope

Benefits

• General Information

Cap base	FA6 [FA6]
Life to 10% failures (nom.)	21000 h
Life to 50% failures (nom.)	26000 h

• Light Technical

Lamp Luminous Flux 25°C EL (Nom)	940 lm
Colour Designation	Cool White (CW)
Lumen maintenance 10,000 hours (nom.)	0 %
Lumen maintenance 2,000 hours (nom.)	88 %
Lumen maintenance 5,000 hours (nom.)	83 %
Chromaticity coordinate X (nom.)	377
Chromaticity coordinate Y (nom.)	381
Colour Temperature, horizontal (Nom)	4100 K
Lamp Luminous Efficacy EM (Nom)	47 lm/W
Colour Rendering Index,horiz (Nom)	63

• Operating and Electrical

Power (Rated) (Nom)	20.0 W
Lamp current (nom.)	0.380 A
Voltage (Nom)	58 V

• Controls and Dimming

Dimmable	yes

• Approval and Application

Energy efficiency label (EEL)	B
Mercury (Hg) content (nom.)	12.0 mg
Energy Consumption kWh/1000 h	25 kWh

• Product Data


Full product code	871150026135940
Order product name	TL-X XL 20W/33-640 SLV/25
EAN/UPC – product	8711500261359
Order code	928037703332
Numerator – quantity per pack	1
Numerator – packs per outer box	25
Material no. (12NC)	928037703332
Net weight (piece)	124.000 g
ILCOS Code	FD-20/41/2B-LC/N-Fa6

PHILIPS

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




Fa6, T12


TL-X XL 20W/33-640

Product	D	A	B	B	C
TL-X XL 20W/33-640 SLV/25	40.5 mm	574 mm	592.5 mm	589 mm	611 mm



Photometric data





© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change