

MASTER TL-D Food

MASTER TL-D Food 18W/79 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Product data

• General Information

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life To 50% Failures (Nom)	15000 h
Life To 50% Failures Preheat (Nom)	20000 h

• Light Technical

Colour Code	79
Luminous Flux (Nom)	740 lm
Colour Designation	Food
Lumen Maintenance 2000 h (Nom)	90 %
Lumen Maintenance 5000 h (Nom)	85 %
Chromaticity Coordinate X (Nom)	365
Chromaticity Coordinate Y (Nom)	314
Colour Temperature, horizontal (Nom)	3800 K
Luminous Efficacy (rated) (Nom)	41 lm/W
Colour Rendering Index horiz (Nom)	74

• Operating and Electrical

Power (Rated) (Nom)	18.0 W
Lamp Current (Nom)	0.360 A
Voltage (Nom)	59 V

• Controls and Dimming

Dimmable	Yes

• Approval and Application

Energy Efficiency Label	B
Mercury (Hg) Content (Nom)	5.0 mg
Energy Consumption kWh/1000 h	23 kWh

• Product Data

Full product code	871150070621840
Order product name	MASTER TL-D Food 18W/79 SLV/25
EAN/UPC - Product	8711500706218
Order code	70621840
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928048002043
Net Weight (Piece)	68.900 g
ILCOS Code	FD-18/38/2A-E-G13


PHILIPS

MASTER TL-D Food

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




TL-D Food 18W/79


Product	D	A	B	B	C
MASTER TL-D Food 18W/79 SLV/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

G13, T8



Photometric data





© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change