

PrimaVision Mini for CDM

HID-PV m PGJ5 20 /I CDM LPF 220-240V

Miniature HID electronic gear for PGJ5 CDM lamps – freeing up the boundaries of creativity and innovation in luminaire design

Product data

• General Information

Application Code	LPF
Type Version	mk1
Lamp Type	CDM
Number Of Lamps	1 piece/unit
Suitable For Outdoor Use	No
Number Of Products On MCB (16A Type B) (Nom)	48

• Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Minimum Mains Voltage Operation (Min)	198 V
Operating Frequency (Nom)	0.10 kHz
Ignition Voltage (Max)	1.5 kV
Ignition Voltage (Min)	1.3 kV
Ignition Switch-Off Time (Nom)	25 min
Mains Voltage Performance (AC)	-10%-+6%
Mains Voltage Safety (AC)	-18%-+10%
Earth Leakage Current (Max)	0.25 mA
Inrush Current Width	0.40 ms
Constant Wattage Deviation	-3%/+3%
Power Losses (Nom)	3 W
Inrush Current Peak (Max)	30 A

• Wiring

Cable Capacity	200 pF
Output Wires Mutual (Nom)	
Cable Length From Device To Lamp	2 m
Wire Striplength	10.0-11.0 mm
Ballast Contact Wire Cross Section	0.75-2.50 mm²
Connector Type	Insert

• System characteristics

Rated Ballast-Lamp Power	20 W

• Temperature

T-Ambient (Max)	50 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	80 °C
T-Storage (Min)	-25 °C
T-Case Lifetime (Nom)	65 °C
T-Case Maximum (Max)	75 °C

• Mechanical and Housing

Housing	/I

PHILIPS

PrimaVision Mini for CDM


- Approval and Application


Active Temperature Protection	Yes
EMI 9 kHz ... 300 MHz	CISPR 15 ed 7.2
Vibration Standard	IEC 68-2-6 Fc
Bumps Standard	IEC 68-2-29 Eb
Approval Marks	F-Marking CE marking CB Certificate
Hum And Noise Level	Inaudible


- Product Data

Full product code	871150090981730
Order product name	HID-PV m PGJ5 20 /I CDM LPF 220-240V
EAN/UPC - Product	8711500909817
Order code	913700601666
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700601666
Net Weight (Piece)	0.140 kg

Dimensional drawing







HID-PV m 20 /GMI CDM HPF

HID-PV m PGJ5 20 /I CDM LPF 220-240V

Product	D1	C1	A1	A2	B1
HID-PV m PGJ5 20 /I CDM LPF 220-240V	4.2 mm	30.0 mm	190.0 mm	154.0 mm	43.3 mm

© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting