

Halogen High Voltage SE (Theater)

6996C 1000W P28s 230V 1CT/10

Two distinctive features make this lamp ideal for use in theater luminaires where long life is essential. Firstly, the filament is especially designed for extended lifetime. Secondly the highly innovative P3 technology, developed by Philips, allows the pinch to better withstand extreme heat conditions which extends the average lamp lifetime, ensures consistent high-quality light output over time, and results in fewer early failures and fewer maintenance man hour costs.

Product data

• General Information

Cap-Base	P28S [P28s]
Philips Code	6996C
ANSI Code	FKD
LIF Code	T/20 (T/14)
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Entertainment
Life To 50% Failures (Nom)	900 h
System Description	P3 Technology

• Light Technical

Luminous Flux (Rated) (Nom)	21000 lm
Correlated Color Temperature (Nom)	3050 K

• Operating and Electrical

Power (Rated) (Nom)	1000 W
Rapid Acting HBC Fuse	6.3 V
Voltage (Nom)	230 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Bulb Finish	Clear
Filament Shape	Bi-Plane
Filament Dimensions WxH	15X13

• Luminaire Design Requirements

Pinch Temperature (Max)	500 °C


• Product Data

Full product code	871150018499325
Order product name	6996C 1000W P28s 230V 1CT/10
EAN/UPC - Product	8711500184993
Order code	923865243228
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	923865243228
Net Weight (Piece)	0.081 kg


PHILIPS

Halogen High Voltage SE (Theater)

Dimensional drawing



P28s



6996C 1000W P28s 230V

Product	D	H	W	L	C
6996C 1000W P28s 230V 1CT/10	23 mm	16 mm	10 mm	55.6 mm	125 mm

© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 23
data subject to change