

HPL

7008 750W Heat Sink 115V 1CT/10

HPL lamps include a barrel-shaped filament that is approved by ETC for use in its Source Four™ fixtures. Bright, high quality light and high beam intensity is assured by the optimal filament design, while the unique P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which extends lifetime and consistency of high-quality light output, resulting in fewer early failures and fewer maintenance man hour costs.

Product data

• General Information

Cap-Base	HEATSINK [Heat Sink]
Philips Code	7008
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Entertainment
Life To 50% Failures (Nom)	300 h
System Description	P3 Technology

• Light Technical

Luminous Flux (Rated) (Nom)	21900 lm
Correlated Color Temperature (Nom)	3250 K
Color Rendering Index (Nom)	100

• Operating and Electrical

Power (Rated) (Nom)	750 W
Rapid Acting HBC Fuse	6.3 V
Voltage (Nom)	115 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Bulb Finish	Clear
Cap-Base Information	Heat Sink
Filament Shape	Bi-Plane
Filament Dimensions WxH	6.3x10.5x6.3

• Luminaire Design Requirements


Pinch Temperature (Max)	500 °C

• Product Data

Full product code	871150018537225
Order product name	7008 750W Heat Sink 115V 1CT/10
EAN/UPC - Product	8711500185372
Order code	924555134428
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	924555134428
Net Weight (Piece)	0.051 kg

PHILIPS


Dimensional drawing



HPL

7008 750W Heat Sink 115V

Product	D	H	W	D1	L	C
7008 750W Heat Sink 115V 1CT/10	19 mm	10.5 mm	6.3 mm	6.3 mm	60.3 mm	104 mm



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting