

Halogen Low Voltage

ELC/10H 250W GX5.3 24V 1CT/24

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.

Product data

• General Information

Cap-Base	GX5.3 [GX5.3]
Philips Code	13163
ANSI Code	ELC/10H
LIF Code	A1/259-10H
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Disco/Theatre
Life To 50% Failures (Nom)	1000 h

• Light Technical

Correlated Color Temperature (Nom)	3400 K
Color Rendering Index (Nom)	100

• Operating and Electrical

Power (Rated) (Nom)	250 W
Voltage (Nom)	24 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Bulb Material	Quartz-UV Open
Reflector Finish	Smooth
Filament Dimensions WxH	-

• Luminaire Design Requirements


Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	400 °C
Working Distance WD	31.7 mm

• Product Data


Full product code	871150043686330
Order product name	ELC/10H 250W GX5.3 24V 1CT/24
EAN/UPC - Product	8711500436863
Order code	924913220540
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	924913220540
Net Weight (Piece)	0.024 kg

PHILIPS

Dimensional drawing



GX5.3, GY5.3, GZ6.35



13163 ELC/10H 250W GX5.3 24V

Product	D	C
ELC/10H 250W GX5.3 24V 1CT/24	50 mm	44.5 mm

© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting