

MASTER PL-L Xtra 4 Pin

MASTER PL-L Xtra 55W/830/4P 1CT/25

MASTER PL-L Xtra is a medium to high-wattage linear compact fluorescent lamp, typically used for general-illumination ceiling luminaires in retail, hospitality and office applications demanding higher lighting levels. MASTER PL-L Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-L lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as HF electronic gear and is provided with a plug-in/pull-out lamp base.

Product data

• General Information

Cap-Base	2G11 [2G11]
Life To 50% Failures	36000 h
Preheat (Nom)	
System Description	High Frequency
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	97 %
LSF Preheat 20000 h Rated	94 %

• Light Technical

Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	4800 lm
Luminous Flux (Rated) (Nom)	4800 lm
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	440
Chromaticity Coordinate Y (Nom)	405
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	87 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	95 %
LLMF 4000 h Rated	94 %
LLMF 6000 h Rated	93 %
LLMF 8000 h Rated	92 %
LLMF 12000 h Rated	91 %
LLMF 16000 h Rated	90 %
LLMF 20000 h Rated	90 %

• Operating and Electrical

Power (Rated) (Nom)	55.0 W
Lamp Current (Nom)	0.525 A

• Temperature

Design Temperature (Nom)	30 °C

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Cap-Base Information	4 Pins

• Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	3.0 mg

PHILIPS

MASTER PL-L Xtra 4 Pin

Energy Consumption kWh/1000 h	61 kWh


- Product Data

Full product code	871150089762640
Order product name	MASTER PL-L Xtra 55W/830/4P 1CT/25
EAN/UPC - Product	8711500897626
Order code	927908883014
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927908883014
Net Weight (Piece)	134.000 g
ILCOS Code	FSDH-55/30/1B-L/P-2G11


Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



2G11, 4P




PL-L Xtra 55W/830/4P

Product	D	D1	A	B	C
MASTER PL-L Xtra 55W/830/4P 1CT/25	39.0 mm	18.0 mm	509.2 mm	535 mm	541.6 mm

MASTER PL-L Xtra 4 Pin

Photometric data



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change