

MASTER PL-T 2 Pin

MASTER PL-T 18W/827/2P 1CT/5X10BOX

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Product data

• General Information

Cap-Base	GX24D-2 [GX24d-2]
Life To 10% Failures (Nom)	6500 h
Life To 50% Failures (Nom)	10000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	98 %
LSF 6000 h Rated	92 %
LSF 8000 h Rated	78 %

• Light Technical

Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	1200 lm
Luminous Flux (Rated) (Nom)	1200 lm
Color Designation	Incandescent White
Chromaticity Coordinate X (Nom)	455
Chromaticity Coordinate Y (Nom)	417
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Min)	67 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	84 %
LLMF 8000 h Rated	81 %

• Operating and Electrical

Power (Rated) (Nom)	18.0 W
Lamp Current (Nom)	0.225 A

• Temperature

Design Temperature (Nom)	28 °C

• Controls and Dimming

Dimmable	No

• Mechanical and Housing

Cap-Base Information	2 Pins

• Approval and Application

Energy Efficiency Label (EEL)	B
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	22 kWh

• Product Data

Full product code	871150055979170
Order product name	MASTER PL-T 18W/827/2P 1CT/ 5X10BOX
EAN/UPC - Product	8711500559791
Order code	927914382771
Numerator - Quantity Per Pack	1

PHILIPS


MASTER PL-T 2 Pin

Numerator - Packs per outer box	50
Material Nr. (12NC)	927914382771
Net Weight (Piece)	59.000 g
ILCOS Code	FSM-18/27/1B-I-GX24d=2


Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




GX24d-2, 2P



PL-T 18W/827/2P M

Product	D	A	B	C
MASTER PL-T 18W/827/2P 1CT/5X10BOX	41 mm	71.8 mm	96.0 mm	119.2 mm

Photometric data



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change