

MASTER CosmoWhite CPO-TT Xtra

MST CosmoWhite CPO-TT Xtra 60W/628 E27

New-generation ceramic metal-halide tubular lamps used in outdoor applications, offering efficient and pleasant white light

Product data

• General Information

Cap-Base	E27
Operating Position	P20 [Parallel +/-20D or Horizontal(HOR)]
Life To 5% Failures (Nom)	21500 h
Life To 10% Failures (Nom)	24000 h
Life To 20% Failures (Nom)	27000 h
Life To 50% Failures (Nom)	32000 h
ANSI Code HID	-
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	99 %
LSF 16000 h Rated	99 %
LSF 20000 h Rated	97 %
LSF 24000 h Rated	90 %
LSF 30000 h Rated	63 %

• Light Technical

Color Code	628 [CCT of 2800K]
Luminous Flux (Rated) (Nom)	7090 lm
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.459
Chromaticity Coordinate Y (Nom)	0.408
Luminous Efficacy (rated) (Nom)	120 lm/W
Color Rendering Index (Nom)	70
LLMF 2000 h Rated	88 %
LLMF 4000 h Rated	86 %
LLMF 6000 h Rated	86 %
LLMF 8000 h Rated	86 %
LLMF 12000 h Rated	85 %
LLMF 16000 h Rated	83 %
LLMF 20000 h Rated	82 %
LLMF 24000 h Rated	80 %
LLMF 30000 h Rated	78 %

• Operating and Electrical

Power (Rated) (Nom)	60.0 W
Re-Ignition Time (Min) (Max)	900 s
Ignition Time (Max)	30 s
Voltage (Max)	98 V
Voltage (Min)	84 V
Voltage (Nom)	91 V

• Controls and Dimming

Dimmable	Yes
Run-Up Time 90% (Max)	3 min

• Mechanical and Housing

Bulb Finish	Clear

• Approval and Application

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	2.0 mg

PHILIPS

MASTER CosmoWhite CPO-TT Xtra

Energy Consumption kWh/1000 h	66 kWh

- UV

Pet (Niosh) (Min)	8 h/500lx
Pet (Niosh) (Nom)	19 h/500lx
Damage Factor D/fc (Nom)	0.170

- Luminaire Design Requirements

Bulb Temperature (Max)	350 °C
Cap-Base Temperature (Max)	200 °C


- Product Data

Full product code	871829169034400
Order product name	MST CosmoWhite CPO-TT Xtra 60W/628 E27
EAN/UPC - Product	8718291690344
Order code	928060109227
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928060109227
Net Weight (Piece)	0.050 kg

Warnings and Safety

- Use only in a totally enclosed luminaire, even during testing (IEC 61167, IEC 62035, IEC 60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with suitable electronic control gear
- Control gear must include end-of-life protection (IEC 61167, IEC 62035)
- E27 lamp holders and other parts in luminaires should be designed to withstand the ignition voltage of the electronic control gear (rated at 5 kV ignition pulse)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



CPO-TT /628




CPO-TT Xtra 60W/628 E27

Product	D	D	O	L	C
MST CosmoWhite CPO-TT Xtra 60W/628 E27	36 mm	35 mm	14 mm	102 mm	156 mm

MASTER CosmoWhite CPO-TT Xtra

Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, January 12
data subject to change