

MSR

MSR 700 1CT/8

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Product data

• General Information

Cap-Base	G22 [G22]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Studio/Disco
Life To 50% Failures (Nom)	1000 h
System Description	-

• Light Technical

Color Code	- [Not Specified]
Luminous Flux (Min)	48000 lm
Luminous Flux (Nom)	55000 lm
Chromaticity Coordinate X (Nom)	325
Chromaticity Coordinate Y (Nom)	320
Correlated Color Temperature (Nom)	5900 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Nom)	75

• Operating and Electrical

Power (Rated) (Nom)	700 W
Lamp Current (Nom)	12 A
Ignition Supply Voltage (Min)	207 V

• Controls and Dimming

Dimmable	No

• Mechanical and Housing

Cap-Base Information	-

• Luminaire Design Requirements

Bulb Temperature (Max)	700 °C
Pinch Temperature (Max)	350 °C

• Product Data


Full product code	872790091575400
Order product name	MSR 700 1CT/8
EAN/UPC - Product	8727900915754
Order code	928078005114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	928078005114
Net Weight (Piece)	0.120 kg

PHILIPS

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




G22


MSR 700

Product	D	O	L	L	L	C	F
MSR 700 1CT/8	30 mm	8.0 mm	74 mm	76 mm	75 mm	152 mm	42 mm



Photometric data





© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 23
data subject to change