

MSR Hot Restrike

MSR 6000 HR UNP/1

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.

Product data

• General Information

Cap-Base	GY38 [GY38]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Indoor & Outdoor filming
Life To 50% Failures (Nom)	300 h
System Description	Hot Restrike

• Light Technical

Color Code	- [Not Specified]
Luminous Flux (Min)	510000 lm
Luminous Flux (Nom)	570000 lm
Chromaticity Coordinate X (Nom)	323
Chromaticity Coordinate Y (Nom)	328
Correlated Color Temperature (Nom)	6000 K
Luminous Efficacy (rated) (Nom)	95 lm/W
Color Rendering Index (Nom)	95

• Operating and Electrical

Power (Rated) (Nom)	6000 W
Lamp Current (Nom)	55 A
Ignition Supply Voltage (Min)	207 V

• Controls and Dimming

Dimmable	Yes

• Mechanical and Housing

Cap-Base Information	-

• Luminaire Design Requirements

Bulb Temperature (Max)	700 °C
Pinch Temperature (Max)	400 °C

• Product Data


Full product code	871150020093800
Order product name	MSR 6000 HR UNP/1
EAN/UPC - Product	8718291548393
Order code	928172705120
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	928172705120
Net Weight (Piece)	0.749 kg

PHILIPS

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




MSR 6000 HR, MSR 12000 HR, MSR 18000 HR


MSR 6000 HR

Product	D	O	L	L	L	C	F	F	F
MSR 6000 HR UNP/1	74 mm	23 mm	208 mm	212 mm	210 mm	375 mm	63 mm	62 mm	61 mm



Photometric data





© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 24
data subject to change