

HPL

7007/LL 575W Heat Sink 240V 1CT/10

HPL lamps include a barrel-shaped filament that is approved by ETC for use in its Source Four™ fixtures. Bright, high quality light and high beam intensity is assured by the optimal filament design, while the unique P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which extends lifetime and consistency of high-quality light output, resulting in fewer early failures and fewer maintenance man hour costs.

Product data

General Information	
Cap-Base	HEATSINK [Heat Sink]
Philips Code	7007/LL
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Entertainment
Life to 50% Failures (Nom)	1500 h
System Description	P3 Technology

Light Technical	
Luminous Flux (Rated) (Nom)	11760 lm
Correlated Color Temperature (Nom)	3050 K
Color Rendering Index (Nom)	100

Operating and Electrical	
Power (Rated) (Nom)	575 W
Rapid Acting HBC Fuse	4 V
Voltage (Nom)	240 V

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	Heat Sink
Filament Shape	Bi-Plane
Filament Dimensions WxH	9.0x12.0

Luminaire Design Requirements	
Pinch Temperature (Max)	480 °C

Product Data	
Full product code	871150018536525
Order product name	7007/LL 575W Heat Sink 240V 1CT/10
EAN/UPC - Product	8711500185365
Order code	924555045528
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	924555045528
Net Weight (Piece)	0.051 kg

HPL

Dimensional drawing



7007/LL 575W Heat Sink 240V

Product	D (max)	H	W	D1	L	C (max)
7007/LL 575W Heat Sink 240V 1CT/10	19 mm	11.5 mm	9.2 mm	8 mm	60.3 mm	104 mm

© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.