

PAR56

PAR56 300W Multipurpose 12V UW 1CT/8

Extremely powerful pressed-glass 179 mm diameter reflector lamps

Product data

General Information	
Cap-Base	MULTIPURPOSE [AKA:Screw Terminal]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Underwater
Nominal Lifetime (Nom)	1000 h
Switching Cycle	4000X

Light Technical	
Beam Angle (Nom)	40 °
Luminous Flux (Rated) (Nom)	4378 lm
Luminous Intensity (Max)	16000 cd
Beam Description	-
Rated Beam Angle	40 °
Correlated Color Temperature (Nom)	2700 K
Color Rendering Index (Nom)	100
Luminous Flux in 90° Cone (Rated)	4378 lm

Operating and Electrical	
Power (Rated) (Nom)	300.0 W
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light
Voltage (Nom)	12 V


Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Efficiency Label (EEL)	C
Energy Consumption kWh/1000 h	318 kWh

Product Data	
Full product code	871150015969442
Order product name	PAR56 300W Multipurpose 12V UW 1CT/8
EAN/UPC - Product	8711500159694
Order code	923804817121
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	923804817121
Net Weight (Piece)	580.000 g
ILCOS Code	IPAR-300-12-179/40

PAR56

Dimensional drawing



PAR56 300W MP 12V UW

Product	D (max)	C (max)	C1
PAR56 300W Multipurpose 12V UW 1CT/8	178.5 mm	119.3 mm	98 mm

© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.