PHILIPS

Lighting



Softone

Softone 11W CDL E27 220-240V 1PF/6

Energy Saving Lamp with Comfort & Design, tailor-made for customers who look for gentle soft light and elegent design, that complement the luminaires beautifully

Product data

General Information	
Cap-Base	E27 [E27]
Nominal Lifetime (Nom)	10000 h
Switching Cycle	30000X

Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux (Nom)	530 lm
Luminous Flux (Rated) (Nom)	530 lm
Color Designation	Cool Daylight
Lumen Maintenance 2000 h (Nom)	83 %
Chromaticity Coordinate X (Nom)	313
Chromaticity Coordinate Y (Nom)	337
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (Rated) (Nom)	48 lm/W
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	65 %

Operating and Electrical	
Input Frequency	50 or 60 Hz
Power (Rated) (Nom)	11.0 W
Lamp Current (Nom)	80 mA
Wattage Equivalent	46 W
Starting Time (Nom)	1.0 s
Warm Up Time to 60% Light (Min)	10 s
Warm Up Time to 60% Light (Max)	100 s
Power Factor (Nom)	0.6
Voltage (Nom)	220-240 V

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	11 kWh


Product Data	
Full product code	871829168204200
Order product name	Softone 11W CDL E27 220-240V 1PF/6
EAN/UPC - Product	8718291682042
Order code	929689118601
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929689118601
Net Weight (Piece)	68.000 g

Softone

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Ambiance 11W CDL E27 220-240V 50/60Hz

Product	D (max)	C (max)	F (max)
Softone 11W CDL E27 220-240V 1PF/6	56.0 mm	109.0 mm	45.5 mm

© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.