

MASTER LEDspot PAR

MASLEDspot D 8.5-75W 840CW PAR30S 25D

With its robust design and warm-white beam of light, these new-generation PAR lamps are ideal for general lighting and spot lighting in the hospitality industry. There is a choice of dimmable and non-dimmable versions. They are especially suitable for public areas such as lobbies, corridors, stairwells, where the light is always on.

Product data

General Information	
Cap-Base	E27 [E27]
Nominal Lifetime (Nom)	40000 h
Switching Cycle	50000X
Technical Type	8-75W

Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	25 °
Light Distribution	Medium beam 25°
Luminous Flux (Nom)	840 lm
Luminous Flux (Rated) (Nom)	840 lm
Luminous Intensity (Nom)	2800 cd
Color Designation	Cool White (CW)
Rated Beam Angle	25 °
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (Rated) (Nom)	94 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	800 lm

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	8.5 W
Lamp Current (Nom)	38 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	A+
Energy Consumption kWh/1000 h	9 kWh


Product Data	
Full product code	871869657807000
Order product name	MASLEDspot D 8.5-75W 840CW PAR30S 25D
EAN/UPC - Product	8718696578070
Order code	929001244202

MASTER LEDspot PAR

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929001244202

Net Weight (Piece)	0.202 kg


Dimensional drawing





PAR30S 230V 8W-75W 675lm 25D 4000K E27 D

Product	D	C
MASLEDspot D 8.5-75W 840CW PAR30S 25D	92 mm	93 mm

Photometric data









© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com
2017, July 25 - data subject to change