PHILIPS

Lighting



MASTER SOX-E

MASTER SOX-E 131W BY22d 1SL/6

Low Pressure Sodium lamp with improved efficacy

Product data

General Information	
Cap-Base	BY22D [BY22d]
Operating Position	P20 [Parallel +/-20D or Horizontal(HOR)]
Life to 5% Failures (Nom)	6000 h
Life to 20% Failures (Nom)	12000 h
Life to 50% Failures (Nom)	18000 h

Light Technical	
Luminous Flux (Rated) (Nom)	26200 lm
Lumen Maintenance 2000 h (Nom)	100 %
Lumen Maintenance 5000 h (Nom)	100 %
Correlated Color Temperature (Nom)	1800 K
Luminous Efficacy (Rated) (Nom)	206 lm/W

Operating and Electrical	
Power (Rated) (Nom)	127.0 W
Lamp Current (EM) (Nom)	0.54 A
Voltage (Nom)	250 V

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Efficiency Label (EEL)	A++
Mercury (Hg) Content (Nom)	0 mg
Energy Consumption kWh/1000 h	140 kWh

Luminaire Design Requirements	
Bulb Temperature (Max)	150 °C
Cap-Base Temperature (Max)	150 °C

Product Data	
Full product code	871150017982110
Order product name	MASTER SOX-E 131W BY22d 1SL/6
EAN/UPC - Product	8711500179821
Order code	928145100008
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	928145100008
Net Weight (Piece)	1.033 kg
ILCOS Code	LSE-E131-BY22d-/H


Warnings and Safety

• Lamps may use electronic or electromagnetic control gear

MASTER SOX-E


Dimensional drawing


Product	D (max)	C (max)
MASTER SOX-E 131W BY22d 1SL/6	66 mm	1120 mm



SOX E 131W BY22d T65


Photometric data






SOX-E

Lifetime





SOX-E

SOX-E



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com
2017, October 19 - data subject to change