

PrimaVision Economy for CDM lamps

HID-PV E 70 /S CDM 220-240V

Single CDM lamp operation, single HID electronic gear – improves cost effectiveness and increases luminaire design flexibility

Product data

General Information	
Type Version	-
Lamp Type	CDM
Number of Lamps	1 piece/unit
Number of Products on MCB (16A Type B) (Nom)	20
Automatic Restart	Yes

Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Minimum Mains Voltage Operation (Min)	180 V
Operating Frequency (Nom)	45-66 kHz
Power Factor 100% Load (Nom)	0.95
Igniton Type	Pulse
Ignition Voltage (Max)	5.0 kV
Ignition Voltage (Min)	3.0 kV
Mains Voltage Performance (AC)	-8%-+6%
Mains Voltage Safety (AC)	180-264V
Inrush Current Width	0.33 ms
Constant Wattage Deviation	Not specified
Power Losses (Nom)	7 W
Inrush Current Peak (Max)	33 A
Output Voltage	- V

Wiring	
Cable Capacity Output Wires Mutual (Nom)	120 pF
Cable Length From Device to Lamp	2 m
Ballast Contact Wire Cross Section	0.50-1.50 mm²
Connector Type	Insert

System characteristics	
Rated Ballast-Lamp Power	70 W

Temperature	
T-Ambient (Max)	50 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	80 °C
T-Storage (Min)	-25 °C
T-Case Lifetime (Nom)	80 °C
T-Case Maximum (Max)	80 °C

Mechanical and Housing	
Housing	/S


PrimaVision Economy for CDM lamps

Approval and Application	
Active Temperature Protection	No
EMI 30 MHz ... 1000 MHz	CISPR15 Edition 7.2
Vibration Standard	IEC68-2-6 F c
Bumps Standard	IEC 68-2-29 Eb
Approval Marks	CE marking ENEC certificate VDE certificate
Surge Test Installation Level	EN61547
Surge Test Performance Criterium	Not specified
Hum And Noise Level	37 dB(A)

Product Data	
Full product code	871829118419500

Order product name	HID-PV E 70 /S CDM 220-240V
EAN/UPC - Product	8718291184195
Order code	913700680966
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700680966
Net Weight (Piece)	0.215 kg

Dimensional drawing



HID-PVe C 70 /S CDM 220-240V 50/60Hz

Product	D1	C1	A1	A2	B1	B2
HID-PV E 70 /S CDM 220-240V	4.9 mm	32.2 mm	109.6 mm	98.5 mm	74.4 mm	63.7 mm

© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.