P DIM PAR16 80 60° 7.2 W/827 GU10

PARATHOM DIM PAR 16 | Dimmable LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product benefits

- Very long lifetime of up to 25,000 h
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Ideal for economical spotlighting

Product features

- Professional LED alternative to high voltage halogen lamps
- Good quality of light; color rendering index R_a: ≥ 80
- High color consistency: ≤ 5 SDCM
- Dimmable (with many common dimmers, see also www.osram.com/dim)
- Made in Germany (versions up to incl. 50 W)
- Mercury-free lamps

© 2018, OSRAM GmbH. All rights reserved.

Technical data

Electrical data

Rated wattage	7.20 W
Nominal wattage	7.20 W
Nominal voltage	220…240 V
Claimed equiv. conventional lamp power	75 W
Power factor λ	> 0.80

Photometrical data


Luminous intensity	790 cd
Rated luminous flux	535 lm
Rated color temperature	2700 K
Color rendering index Ra	80
Light color (designation)	Warm White
Standard deviation of color matching	≤5 sdcm
Nominal luminous flux	535 lm
Nominal useful luminous flux 90°	535 lm
Rated useful luminous flux 90°	535 lm
Rated peak intensity	790 cd
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Beam angle	60 °
Warm-up time (60 %)	< 0.50 s
Nominal beam angle	60 °
Rated beam angle (half peak value)	60.00 °
Starting time	< 0.5 s

© 2018, OSRAM GmbH. All rights reserved.

Dimensions & weight



Overall length	55.0 mm
Diameter	51.0 mm
Outer bulb	PAR51
Length	55.0 mm
Maximum diameter	51.0 mm

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes
Appropriate disposal acc. to WEEE	Yes
Product remark	All technical parameters apply to the entire lampDue to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes

Certificates & standards

Energy efficiency class	A+

© 2018, OSRAM GmbH. All rights reserved.

Energy consumption	8 kWh/1000h

Country specific categorizations

ILCOS	DRPAR-7,2/827-220-240-GU10-50/60
Order reference	LPPAR16D8060 7,

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075056626	P DIM PAR16 80 60° 7.2 W/827 GU10	Shipping carton box 10 Pieces Folding carton box	255 mm x 107 mm x 72 mm	1.96 dm^3	678.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For dimming conformity see
- www.osram.com/DIM

For further products and actual information concerning LED lamps see
- www.osram.com/ledlamps

For Guarantee see
- www.osram.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, OSRAM GmbH. All rights reserved.