HMI 250 W/SE

HMI | Metal halide lamps, single-ended



Areas of application

- Film and television recording in daylight conditions, in the studio or outdoors
- Film and TV production (high-wattage lamps)
- Stage (lighting for dramatic effect)
- Entertainment

Product benefits

- Very high luminous efficacy of up to 100 lm/W

Product features

- Color temperature: approx. 6,000 K (Daylight)
- Hot restart capability
- High color rendering index: R_a >







© 2018, OSRAM GmbH. All rights reserved.

Technical data

Electrical data

Nominal voltage	50.0 V
Lamp voltage	50 V
Nominal current	5.4 A
Nominal wattage	250.00 W

Photometrical data

Nominal luminous flux	16200 lm
Color temperature	6000 K
Color rendering index Ra	90

Dimensions & weight





Diameter	12.0 mm
Length	84.0 mm
Light center length (LCL)	39.0 mm

Lifespan

Lifespan	250 h

Additional product data

Base (standard designation)	FaX1.5

Capabilities

Burning position	Any

Certificates & standards

EEI – Energy Label	B

© 2018, OSRAM GmbH. All rights reserved.

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300239064	OSRHMI250SE	-	-	-

© 2018, OSRAM GmbH. All rights reserved.

Safety advice

Because of their high luminance, UV radiation (does not apply to HMI UVS) and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation of standard HMI lamps is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.



p 45

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300239064	HMI 250 W/SE	Shipping carton box 1	202 mm x 142 mm x 150 mm	4.30 dm^3	611.75 g
4050300730363	HMI 250 W/SE	Shipping carton box 10	235 mm x 210 mm x 225 mm	11.10 dm^3	1227.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, OSRAM GmbH. All rights reserved.