PP MR16 35 36° 6.1 W/940 GU5.3

PARATHOM PRO MR16 | Dimmable low-voltage LED reflector lamps MR16 with retrofit pin base



Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product benefits

- Short payback period thanks to low energy consumption and maintenance costs
- Premium light quality thanks to high color rendering index and narrow binning
- Easy replacement of halogen lamps due to compact full glass design and single optic

Product features

- Very high color rendering (R_a: 90)
- Very high color consistency: ≤ 4 SDCM
- Dimmable (with many common dimmers, see also www.osram.com/dim)
- Made in Germany (versions up to 20 W)
- Mercury-free lamps

© 2018, OSRAM GmbH. All rights reserved.

Technical data

Electrical data

Rated wattage	6.10 W
Nominal wattage	6.10 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	35 W
Power factor λ	> 0.70

Photometrical data


Luminous intensity	900 cd
Rated luminous flux	350 lm
Rated color temperature	4000 K
Color rendering index Ra	≥90
Light color (designation)	Cool White
Standard deviation of color matching	≤3 sdcm
Nominal luminous flux	350 lm
Nominal useful luminous flux 90°	350 lm
Rated useful luminous flux 90°	350 lm
Rated peak intensity	900 cd
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Nominal beam angle	36 °
Rated beam angle (half peak value)	36.00 °
Starting time	< 0.5 s

© 2018, OSRAM GmbH. All rights reserved.

Dimensions & weight



Overall length	46.0 mm
Diameter	51.0 mm
Outer bulb	MR51
Length	46.0 mm
Maximum diameter	51.0 mm

Lifespan

Nominal lamp life time	40000 h
Rated lamp life time	40000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	GU5.3
Mercury content	0.0 mg
Mercury-free	Yes
Appropriate disposal acc. to WEEE	Yes
Product remark	All technical parameters apply to the entire lampDue to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes

Certificates & standards

Energy efficiency class	A

© 2018, OSRAM GmbH. All rights reserved.

Energy consumption	6 kWh/1000h

Country specific categorizations

ILCOS	DRR-6,1/940-12-GU5,3-50/36
Order reference	LPMR16D3536 6,1

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075815452	PP MR16 35 36° 6.1 W/940 GU5.3	Shipping carton box 10 Pieces Folding carton box	255 mm x 107 mm x 72 mm	1.96 dm^3	498.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For dimming conformity see
- www.osram.com/DIM

For further products and actual information concerning LED lamps see
- www.osram.com/ledlamps

For Guarantee see
- www.osram.com/guarantee

Further information see
- www.osram.com/low-voltage-ledlamps

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, OSRAM GmbH. All rights reserved.