HNS 4 W G5

PURITEC HNS | Germicidal ultraviolet lamps



Areas of application

- Efficient disinfecting of air, water and surfaces

Product benefits

- Effective and environment-friendly disinfection without chemicals
- Low mercury content
- Long lifetime due to specific coating
- Ozone-free

Product features

- Dominant wavelength: 254 nm (OFR version)







© 2018, OSRAM GmbH. All rights reserved.

Technical data


Electrical data

Nominal voltage	29.0 V
Construction voltage	29.00 V
Nominal current	0.17 A
Lamp current	0.17 A
Nominal wattage	4.00 W

Photometrical data

Radiated power 200...280 nm (UVC)	0.9 W

Dimensions & weight



Diameter	16.0 mm
Length	136.0 mm

Lifespan

Lifespan	6000 h

Additional product data

Base (standard designation)	G5

Capabilities

Dimmable	No
Burning position	Any

Country specific categorizations

Order reference	HNS 4W G5

© 2018, OSRAM GmbH. All rights reserved.

Country specific information

Product code	METEL-Code	SEG-No.	STK number	UK Org
4008321378316	-	-	4834800	-

© 2018, OSRAM GmbH. All rights reserved.

Safety advice

PURITEC germicidal lamps emit high-intensity UV radiation that can cause sunburn and conjunctivitis. The skin and eyes must therefore not be exposed to direct or reflected unfiltered radiation.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321378316	HNS 4 W G5	Sleeves 1	154 mm x 19 mm x 19 mm	0.06 dm^3	17.99 g
4008321378323	HNS 4 W G5	Shipping carton box 25	165 mm x 117 mm x 109 mm	2.10 dm^3	499.65 g
4008321806055	HNS 4 W G5	Shipping carton box 400	166 mm x 118 mm x 106 mm	2.08 dm^3	516.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, OSRAM GmbH. All rights reserved.