PRODUCT DATASHEET
O BOLLARD 800 POLE 6 W 3000 K IP44 SST

OUTDOOR BOLLARD POLE | Stainless steel bollards with indirect illumination



AREAS OF APPLICATION

- Outdoor
- Pathway lighting
- Driveways

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Special light guide design for low-glare illumination

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP44
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminares
- Diffuser made of transparent polycarbonate



© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Operating mode	Mains voltage
Mains frequency	50/60 Hz
Power factor λ	>0.5
Nominal wattage	6.00 W
Nominal voltage	220...240 V
Nominal current	0.06 A


Photometrical data

Color temperature	3000 K
Luminous efficacy	60 lm/W
Luminous flux	360 lm
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	<6 sdcm

Light technical data

Beam angle	160 °

Dimensions & weight



Diameter	102.0 mm
Height	800.0 mm
Product weight	1500.00 g

Colors & materials

Housing color	Steel
Product color	Steel
Body material	Stainless steel

© 2018, LEDVANCE GmbH. All rights reserved.

Temperatures & operating conditions

Ambient temperature range	-20…40 °C

Lifespan

Number of switching cycles	15000
Lifespan L70 at 25 °C	30000 h

Additional product data

Mounting type	Surface
Mounting location	Ground
Product remark	Available from February 2018

Capabilities


Dimmable	No
Type of connection	Terminal, 2-Pole (L, N)
LED module replaceable	Not replaceable

Certificates & standards

Type of protection	IP44
Protection class	II
Protection class IK (shock resistance)	IK06
Photobiological safety group	RG 0
Standards	CE

© 2018, LEDVANCE GmbH. All rights reserved.

Light Distribution



LDC typ polar

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075153	O BOLLARD 800 POLE 6 W 3000 K IP44 SST	Shipping carton box 2	835 mm x 175 mm x 320 mm	46.76 dm^3	3921.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.