PRODUCT DATASHEET
ST8AU-EM 15 W/3000 K 1200 mm

SubstiTUBE Advanced Ultra Output | LED tubes for electromagnetic control gears



AREAS OF APPLICATION

- General illumination within ambient temperatures from −20…+50 °C
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores

PRODUCT BENEFITS

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- Energy savings of up to 63 % (compared to T8 fluorescent lamp on CCG)
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Very high resistance to switching loads
- Also suitable for operation at low temperatures
- High luminous flux for sophisticated lighting tasks

PRODUCT FEATURES

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Rotatable end caps
- For especially uniform illumination
- Lifetime: up to 60,000 h
- Mercury-free and RoHS compliant



© 2018, LEDVANCE GmbH. All rights reserved.

- Type of protection: IP20
- Tube made of glass

TECHNICAL DATA

Electrical data

Rated wattage	15.00 W
Nominal voltage	220…240 V
Operating frequency	50…60 Hz
Nominal wattage	15.00 W
Nominal current	0.069 A
Type of current	AC
Power factor λ	> 0.90


Photometrical data


Rated color temperature	3000 K
Nominal luminous flux	2160 lm
Rated luminous flux	2160 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Luminous flux	2160 lm
Color rendering index Ra	>80
Standard deviation of color matching	≤4 sdcm

Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s
Rated beam angle (half peak value)	210.00 °

Dimensions & weight





© 2018, LEDVANCE GmbH. All rights reserved.

Length with base excl. base pins/connection	1200.00 mm
Product weight	198.00 g
Overall length	1213 mm

Temperatures & operating conditions

Ambient temperature range	-20…+50 °C

Lifespan

Lifespan	60000 h
Nominal lamp life time	60000 h
Rated lamp life time	60000 h
Number of switching cycles	200000

Additional product data

Base (standard designation)	G13
Mercury-free	Yes
Product remark	When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system/Not usable in luminaires with serial lamp connection, i.e. more than one tube at one magnetic ballast (tandem circuitry)

Capabilities

Dimmable	No

Certificates & standards

Type of protection	IP20
Standards	CE; VDE
Energy efficiency class	A++
Energy efficiency class	A++
Energy consumption	15 kWh/1000h

Country-specific categorizations

ILCOS	DR-15/830-G13-25.5/1213
Order reference	ST8AU-1.2M 15W/

Logistical data

Temperature range at storage	-20…80 °C

EQUIPMENT / ACCESSORIES

– Suitable for operation with low-loss and conventional control gears

© 2018, LEDVANCE GmbH. All rights reserved.

SAFETY ADVICE

Not suitable for operation with electronic control gear.
Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075818279	ST8AU-EM 15 W/3000 K 1200 mm	Shipping carton box 10	1352 mm x 210 mm x 115 mm	32.65 dm^3	3170.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

LEGAL ADVICE

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.