PRODUCT DATASHEET
ORBIS Tray Sparkle 900 85 W Remote-CCT

ORBIS Tray Sparkle | LED Luminaire with sparkling effect and nickel ring



AREAS OF APPLICATION

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

PRODUCT BENEFITS

- Very homogenous light
- Easy and quick installation

PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Housing surface made of brushed nickel
- Color temperature adjustment, dimming and night functions via remote control

© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	85.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	2700...6500 K
Color rendering index Ra	>80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	4800 lm

Dimensions & weight



Diameter	900.0 mm
Height	200.0 mm
Product weight	4800.00 g

Colors & materials

Body material	Metal
Housing color	Gray
Product color	Gray
Cover material	Polymethylmethacrylate (PMMA)

Additional product data

Mounting type	Surface
Mounting location	Ceiling

Capabilities

Dimmable	Yes

© 2018, LEDVANCE GmbH. All rights reserved.

Type of connection	Terminal

Certificates & standards

Protection class	III
Type of protection	IP20
Standards	CE

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075048393	ORBIS Tray Sparkle 900 85 W Remote-CCT	Shipping carton box 1	200 mm x 980 mm x 980 mm	192.08 dm^3	8140.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.