PRODUCT DATASHEET
TubeKIT LED 0.6 8,9 W 830

TubeKIT | Mobile LED batten luminaire



AREAS OF APPLICATION

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Shelves, furniture integration or under cabinet mounting
- Direct or indirect lighting (e.g. cove lighting)
- Kitchens, workspaces

PRODUCT BENEFITS

- Easy to use and multifunctional LED batten luminaire
- All required accessories included (screws, dowels, brackets, hook)
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Bright, robust and durable
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Homogeneous light output

PRODUCT FEATURES

- Durable and energy-saving LED luminaire
- Mercury-free and RoHS compliant
- Clip-In technology for stationary use and hook for mobile use
- Lifetime: up to 30,000 h
- Not dimmable
- Polycarbonate housing



© 2018, LEDVANCE GmbH. All rights reserved.

- Uniform illumination
- Available with luminous flux up to 750 lm, 1,700 lm, 2,000 lm (model dependent)
- Color temperatures: 3,000 K, 4,000 K
- Color rendering index R_a: ≥ 80

TECHNICAL DATA

Electrical data

Nominal wattage	8.9 W
Nominal voltage	220…240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	>80
Light color (designation)	Warm white
Luminous flux	720 lm

Dimensions & weight

Length	600.0 mm
Width	35.0 mm
Diameter	30.0 mm
Height	36.5 mm
Product weight	183.00 g

Colors & materials

Body material	Polycarbonate (PC)
Housing color	White
Product color	White

Temperatures & operating conditions

Ambient temperature range	-20…+45 °C

Lifespan

Lifespan	30000 h

Additional product data

Mounting type	Surface
Mounting location	Ceiling / Wall

Capabilities

Dimmable	No

© 2018, LEDVANCE GmbH. All rights reserved.

Type of connection	Cable with Euro plug
Holder designation	G5

Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899948068	TubeKIT LED 0.6 8,9 W 830	Shipping carton box 8	934 mm x 286 mm x 110 mm	29.38 dm^3	3317.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.