PRODUCT DATASHEET
LINEAR LED TURN 6 W 3000 K

Linear LED Turn | Undercabinet luminaire with tilt function



AREAS OF APPLICATION

- Undercabinet lighting
- For indoor use only

PRODUCT BENEFITS

- Easy and quick series connection thanks to simple plug system
- Very homogenous light
- Connection of up to 10 luminaires in a row

PRODUCT FEATURES

- Housing material: aluminum

© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	6.00 W
Operating mode	Integrated LED driver
Nominal voltage	100...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	>80
Light color (designation)	Warm White
Luminous flux	380 lm

Dimensions & weight



Length	357.0 mm
Width	60.0 mm
Height	24.0 mm
Product weight	318.00 g

Colors & materials

Body material	Aluminum
Housing color	Silver
Product color	Silver
Cover material	Polycarbonate (PC)

Lifespan

Lifespan	30000 h

Additional product data

© 2018, LEDVANCE GmbH. All rights reserved.

Mounting type	Surface
Mounting location	Cabinet undersides

Capabilities

Dimmable	No
Type of connection	Plug, EU

Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/REACH/RoHS

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075026520	LINEAR LED TURN 6 W 3000 K	Shipping carton box 20	442 mm x 363 mm x 185 mm	29.68 dm^3	8506.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.