PRODUCT DATASHEET
SIG 1541

High-voltage krypton lamps, road traffic



AREAS OF APPLICATION

- Road traffic signalling systems

PRODUCT BENEFITS

- Excellent optical efficiency thanks to a small cradle diameter
- High luminous efficacy from krypton as filler gas
- Max. premature failure rate: 2 % up to 3,000 h (related to lamp failures only)
- High resistance to shock and vibration thanks to nine supports for the filament

PRODUCT FEATURES

- Lamp base resistant to corrosion
- Long average lamp lifetime: 8,000 h
- Maintenance intervals up to four months possible (depending on installation)

© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	60.00 W
Nominal voltage	230...240 V
Test voltage	235 V

Photometrical data

Nominal luminous flux	380 lm
Color temperature	2700 K
Luminous flux	380 lm
Color rendering index Ra	100

Dimensions & weight





E27
IEC 7004-21

Diameter	62.0 mm
Overall length	91.0 mm
Light center length (LCL)	69.0 mm [1)]

[1)] Distance from the coil to the top of base

Additional product data

Base (standard designation)	E27

Capabilities

Burning position	s105 [1)]

[1)] Only the permissible burning position may be used otherwise the lamp will fail prematurely

Certificates & standards

Energy efficiency class	E

Country-specific categorizations

Order reference	SIG 1541 CL 60W

© 2018, LEDVANCE GmbH. All rights reserved.

COUNTRY SPECIFIC INFORMATION

Product code	METEL code	SEG-No.	STK number	UK Org
4050300405049	OSRSIG1541	-	4733761	-

© 2018, LEDVANCE GmbH. All rights reserved.

SAFETY ADVICE

Use only in signal equipment/luminaires that are specially designed for the purpose.
Protect the lamps against moisture during operation and installation.



LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300405049	SIG 1541	Folding carton box 1	91 mm x 58 mm x 58 mm	0.31 dm^3	42.00 g
4050300405056	SIG 1541	Shipping carton box 100	591 mm x 197 mm x 301 mm	35.04 dm^3	4580.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

LEGAL ADVICE

Correspond to DIN 49842 part 1 and 3
Meet luminous intensity requirements of DIN 67527-1/EN 12368 (depending on installation)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.