PRODUCT DATASHEET
SubMARINE Integrated 18 W 0.6 m

SubMARINE Integrated | Damp-proof luminaires with integrated LED module



AREAS OF APPLICATION

- Basements, garages, warehouses

PRODUCT BENEFITS

- Easy and quick installation
- Very homogenous light
- 3 years guarantee
- Extremely bright

PRODUCT FEATURES

- Dust-protected and jet-proof (IP65)
- Not dimmable

© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	18.00 W
Operating mode	Integrated LED driver
Nominal voltage	220…240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	1500 lm
Luminous efficacy	88 lm/W

Dimensions & weight



Length	590.0 mm
Width	86.0 mm
Height	66.0 mm
Product weight	670.00 g

Colors & materials

Body material	Polycarbonate (PC)
Housing color	Gray
Product color	Gray

Temperatures & operating conditions

Ambient temperature range	-20…35 °C

Additional product data

© 2018, LEDVANCE GmbH. All rights reserved.

Mounting type	Surface
Mounting location	Ceiling / Wall

Capabilities

Dimmable	No
Type of connection	Terminal, 2-Pole (L, N)

Certificates & standards

Protection class	II
Type of protection	IP65
Standards	CE/REACH/RoHS

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075026469	SubMARINE Integrated 18 W 0.6 m	Shipping carton box 8	640 mm x 200 mm x 304 mm	38.91 dm^3	6866.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- www.osram-lamps.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.