PRODUCT DATASHEET
PANEL 600 DALI UGR<19 36 W 4000 K MP WT

PANEL 600 DALI UGR < 19 | Square edge-lit panel luminaires with DALI driver, low glare, 600 mm

AREAS OF APPLICATION

- Direct replacement for luminaires with fluorescent lamps
- Corridors
- Offices
- Conference rooms
- Reception areas
- Foyers
- Suitable for recessed ceiling systems with grid size of 600 x 600 mm

PRODUCT BENEFITS

- Good glare reduction (UGR < 19)
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- Advanced functionality due to already included DALI driver
- DALI driver with individual luminaire current set-up already installed
- Light guide plate with micro structure made of non-yellowing material for long lifetime
- Easy and quick installation
- 5 years guarantee

PRODUCT FEATURES

- Lifetime (L80/B50): up to 60,000 h (at 25 °C)
- Aluminum housing, polystyrene diffuser
- High luminous efficacy: up to 120 lm/W
- Initial color consistency: < 4 SDCM
- Ambient temperature in operation: -10...+40 °C



© 2018, LEDVANCE GmbH. All rights reserved.

– Type of protection: IP20

TECHNICAL DATA

Electrical data

Nominal wattage	36.00 W
Operating mode	Electronic control gear (ECG)
Nominal voltage	220…240 V
Mains frequency	50/60 Hz
Power factor λ	>0.90


Photometrical data


Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	4320 lm
Luminous efficacy	120 lm/W
Standard deviation of color matching	<4 sdcm

Light technical data

Beam angle	90.00 °
UGR lateral	<19
UGR longitudinal	<19

Dimensions & weight





Length	595.0 mm
Width	595.0 mm
Height	12.2 mm
Product weight	3250.00 g

Colors & materials

© 2018, LEDVANCE GmbH. All rights reserved.

Housing color	White
Product color	White
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)

Temperatures & operating conditions

Ambient temperature range	-10…40 °C

Lifespan

Lifespan L70 at 25 °C	70000 h
Lifespan L80 at 25 °C	60000 h
Lifespan L90 at 25 °C	35000 h

Additional product data

Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling
Product remark	Available from July 2018

Capabilities


Dimmable	Yes
Type of connection	Cable, 3-pole
LED module replaceable	Not replaceable

Certificates & standards


Type of protection	IP20
Protection class	II
Protection class IK (shock resistance)	IK03
Photobiological safety group	RG 0
Standards	CE/CB/ENEC/TÜV SÜD/RoHS

© 2018, LEDVANCE GmbH. All rights reserved.

Light Distribution



LDC typ cone



LDC typ polar

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- Security rope for luminaire included
- External control gear included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075113305	PANEL 600 DALI UGR<19 36 W 4000 K MP WT	Shipping carton box 4	720 mm x 195 mm x 669 mm	93.93 dm^3	15461.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.