PRODUCT DATASHEET
SPOT FP FIX DIM 8 W 4000 K IP44 SI

SPOT DIM | Recessed mounted spotlight, round shape, dimmable



AREAS OF APPLICATION

- Replacement of halogen lamp spotlights
- General illumination
- Hotel rooms
- Bars, restaurants
- Accent lighting
- Galleries, museums
- Residential interiors

PRODUCT BENEFITS

- High luminous efficacy
- Design matches the LEDVANCE DOWNLIGHT luminaire family
- Energy savings of up to 90 % compared to halogen lamp spotlights
- Functional and minimalistic design
- Easy and quick installation
- External driver for extended flexibility (compatible with selected DALI drivers)
- 3 years guarantee

PRODUCT FEATURES

- Initial color consistency: ≤ 4 SDCM
- Housing material: aluminum
- Lens material: PMMA



© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	8.00 W
Operating mode	Electronic control gear (ECG)
Nominal voltage	220...240 V
Power factor λ	>0.90
Mains frequency	50/60 Hz


Photometrical data

Color temperature	4000 K
Luminous flux	670 lm
Luminous efficacy	80 lm/W
Standard deviation of color matching	≤4 sdcm
Light color (designation)	Cool White
Color rendering index Ra	>80

Light technical data

Beam angle	36 °

Dimensions & weight



Diameter	81.0 mm
Height	51.0 mm
Product weight	268.00 g
Mounting diameter	68 mm

Colors & materials

Body material	Aluminum
Housing color	Silver
Product color	Silver

© 2018, LEDVANCE GmbH. All rights reserved.

Temperatures & operating conditions

Ambient temperature range	-20…45 °C

Lifespan

Lifespan L70 at 25 °C	50000 h
Lifespan L80 at 25 °C	40000 h
Lifespan L90 at 25 °C	20000 h

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities


Dimmable	Yes
Type of connection	Terminal, 2-pin
LED module replaceable	Not replaceable

Certificates & standards


Protection class IK (shock resistance)	IK06
Photobiological safety group	RG 0
Protection class	II
Type of protection	IP44
Standards	CE/CB/TÜV SÜD/EAC/RoHS

© 2018, LEDVANCE GmbH. All rights reserved.

Light Distribution



LDC typ cone



LDC typ polar

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075127067	SPOT FP FIX DIM 8 W 4000 K IP44 SI	Shipping carton box 27	440 mm x 320 mm x 360 mm	50.69 dm^3	10083.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.