PRODUCT DATASHEET
HQL LED 2700 lm 23 W/2700 K E27

HQL LED | LED replacement for HID lamps for outdoor application



AREAS OF APPLICATION

- Streets
- Area lighting
- Pedestrian zones
- Parks
- Industry
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Saves up to 78 % energy when used as replacement for mercury vapor lamps (HQL)
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- LED alternative for applications requiring a high luminous flux
- Power factor: 0.9
- Type of protection: IP65
- High surge protection: up to 4 kV (L-N)
- Replacement for HQL: Suitable for operation with conventional control gear for HQL
- Replacement for other HID: Suitable for operation with line voltage without control gear



© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Rated wattage	23.00 W
Nominal wattage	23.00 W
Nominal voltage	220…240 V
Operating frequency	50…60 Hz
Power factor λ	> 0.90


Photometrical data


Nominal luminous flux	2700 lm
Rated luminous flux	2700 lm
Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	2700 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Color rendering index Ra	≥80

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight





Overall length	145.0 mm
Diameter	75.0 mm
Outer bulb	-
Length	145.0 mm

© 2018, LEDVANCE GmbH. All rights reserved.

Temperatures & operating conditions

Maximum temperature at tc test point	92 °C

Lifespan

Nominal lamp life time	50000 h
Rated lamp life time	50000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Show WEEE picto	Yes

Capabilities

Dimmable	No

Certificates & standards

Energy efficiency class	A+
Energy efficiency class	A+
Energy consumption	23 kWh/1000h

Country-specific categorizations

Order reference	HQLLED2700 23W/

SAFETY ADVICE

The bulb may be larger and heavier than the replaced bulb. Before installation it must be checked, if the luminaire and especially the holder is capable of carrying the weight of the lamp.
Not suitable for operation with ignitors
Operation on the capacitor can lead to a reduction of the power factor of the system.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075124806	HQL LED 2700 lm 23 W/2700 K E27	Shipping carton box 6	288 mm x 196 mm x 193 mm	10.89 dm^3	2922.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2018, LEDVANCE GmbH. All rights reserved.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.