# PRODUCT DATASHEET
# P CLAS B 60 FR 6 W/2700 K E14

## PARATHOM Retrofit CLASSIC B DIM | Dimmable LED lamps, classic bulb shape




### AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

### PRODUCT BENEFITS

- Design, dimensions, luminous flux comparable to an incandescent lamp
- Very low energy consumption
- Robust against vibrations
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

### PRODUCT FEATURES

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 300°




© 2018, LEDVANCE GmbH. All rights reserved.

## TECHNICAL DATA

### Electrical data

| | |
|---|---|
| **Rated wattage** | 6.00 W |
| **Nominal wattage** | 6.00 W |
| **Nominal voltage** | 220…240 V |
| **Operating frequency** | 50…60 Hz |
| **Power factor λ** | > 0.50 |
| **Claimed equiv. conventional lamp power** | 60 W |


### Photometrical data

| | |
|---|---|
| **Nominal luminous flux** | 806 lm |
| **Rated luminous flux** | 806 lm |
| **Rated color temperature** | 2700 K |
| **Lumen main.fact.at end of nom.life time** | 0.70 |
| **Light color (designation)** | Warm White |
| **Color temperature** | 2700 K |
| **Luminous flux** | 806 lm |
| **Color rendering index Ra** | ≥80 |
| **Standard deviation of color matching** | ≤6 sdcm |

### Light technical data

| | |
|---|---|
| **Warm-up time (60 %)** | < 0.50 s |
| **Starting time** | < 0.5 s |

### Dimensions & weight




| | |
|---|---|
| **Overall length** | 118.0 mm |
| **Diameter** | 35.0 mm |
| **Outer bulb** | B35 |
| **Length** | 118.0 mm |


© 2018, LEDVANCE GmbH. All rights reserved.

## Temperatures & operating conditions

| | |
|---|---|
| **Maximum temperature at tc test point** | 65 °C |

## Lifespan

| | |
|---|---|
| **Nominal lamp life time** | 15000 h |
| **Rated lamp life time** | 15000 h |
| **Number of switching cycles** | 100000 |

## Additional product data

| | |
|---|---|
| **Base (standard designation)** | E14 |
| **Mercury content** | 0.0 mg |
| **Mercury-free** | Yes |
| **Design / version** | Frosted |
| **Show WEEE picto** | Yes |
| **Product remark** | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

## Capabilities

| | |
|---|---|
| **Dimmable** | Yes |

## Certificates & standards

| | |
|---|---|
| **Energy efficiency class** | A++ |
| **Energy efficiency class** | A++ |
| **Energy consumption** | 5 kWh/1000h |

## Country-specific categorizations

| | |
|---|---|
| **ILCOS** | DRBB/F-5/827-220-240-E14-35 |
| **Order reference** | LEDPCLB60D 6W/8 |

## LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---|---|---|---|---|---|
| 4058075101258 | P CLAS B 60 FR 6 W/2700 K E14 | Shipping carton box 10 | 205 mm x 87 mm x 123 mm | 2.19 $dm^3$ | 458.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER


© 2018, LEDVANCE GmbH. All rights reserved.

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.


© 2018, LEDVANCE GmbH. All rights reserved.