PRODUCT DATASHEET
ST8SP-EM 7.6 W/3000 K 600 mm EM

SubstiTUBE STAR PC | Economic LED tubes for electromagnetic control gears



AREAS OF APPLICATION

- Corridors, stairways, parking garages
- Cooling and storage rooms
- Warehouses
- Domestic applications
- General illumination within ambient temperatures from –20…+45 °C

PRODUCT BENEFITS

- Extremely break resistant thanks to cover made of polycarbonate
- High color homogeneity
- Energy savings of up to 68 % compared to conventional 1,500 mm T8 fluorescent lamp
- Instant flickerfree starting

PRODUCT FEATURES

- T8 LED tube with G13 base
- Mercury-free and RoHS compliant
- Luminous efficacy: up to 105 lm/W
- Type of protection: IP20



© 2018, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Rated wattage	7.60 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal wattage	7.60 W
Nominal current	0.035 A
Type of current	AC
Power factor λ	> 0.90


Photometrical data


Rated color temperature	3000 K
Nominal luminous flux	720 lm
Rated luminous flux	720 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Luminous flux	720 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm

Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s
Rated beam angle (half peak value)	190.00 °

Dimensions & weight





Length with base excl. base pins/connection	590.00 mm
Tube diameter	27.2 mm

© 2018, LEDVANCE GmbH. All rights reserved.

Product weight	66.00 g
Overall length	603.0 mm

Temperatures & operating conditions

Ambient temperature range	-20…+45 °C

Lifespan

Lifespan	30000 h
Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Number of switching cycles	200000

Additional product data

Base (standard designation)	G13
Mercury-free	Yes

Capabilities

Dimmable	No

Certificates & standards

Type of protection	IP20
Standards	CE/CB
Energy efficiency class	A+
Energy efficiency class	A+
Energy consumption	8 kWh/1000h

Country-specific categorizations

ILCOS	DR-7.6/830-G13-27.5/600
Order reference	ST8SP-0.6M 7,6W

Logistical data

Temperature range at storage	-20…80 °C

EQUIPMENT / ACCESSORIES

- Suitable for operation on magnetic control gear

SAFETY ADVICE

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

© 2018, LEDVANCE GmbH. All rights reserved.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075820197	ST8SP-EM 7.6 W/3000 K 600 mm EM	Shipping carton box 8	724 mm x 148 mm x 88 mm	9.43 dm^3	1119.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

LEGAL ADVICE

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2018, LEDVANCE GmbH. All rights reserved.